

Product data sheet

Specifications



Acti9 PowerTag Link Display, color display, DIN rail

A9XMWRD

Main

Range	Acti9
Product or component type	Display
Device application	Human-machine dialogue application
Range compatibility	Acti9 PowerTag Link smart communication module
Display type	LCD

Complementary

Display colour	Color
Display resolution	320 x 240 pixels QVGA
Display size	2 inch
Information displayed	Current Voltage Active power Power factor Energy consumption Alarms
Control type	4 x push-button
[Us] rated supply voltage	110...277 V AC 24 V DC
Power consumption in W	2.7 W
Connector type	Terminal block
Provided equipment	Power supply
Mounting mode	Rail Flush-mounted
Mounting support	DIN rail Framework
Width	72 mm
Height	95 mm
Embedding depth	49.5 mm
Projecting depth	18.5 mm
Net weight	137 g

Environment

IP degree of protection	IP41 conforming to IEC 60529 (on flush mounting)
-------------------------	--

Relative humidity	5...95 % at 45 °C
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Standards	EN 61326 EN 300-328 EN 301-489-1 EN 301-489-17
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	224.0 g
Package 1 Height	8.0 cm
Package 1 width	8.0 cm
Package 1 Length	11.0 cm
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Weight	6.445 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm
Unit Type of Package 3	P06
Number of Units in Package 3	324
Package 3 Weight	86.044 kg
Package 3 Height	105.0 cm
Package 3 width	80.0 cm
Package 3 Length	60.0 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information