Product data sheet Characteristics

5000ETP10W

C-Bus - Ethernet touch panel - 10" - white cover frame





Main Range C-Bus Product or component Touch panel type Device application Equipment monitoring and control Display colour 262000 colours 10.1 inch Display size Provided equipment 1 mounting plate 1 cover frame 10 fixing screws 4 washer 1 screw 1 desk stand 1 micro SD card securing plate 1 Ethernet cable securing plate

White

Complementary

Supply	External power supply: 12 V DC, +/- 5 %, <1.5 A Via PoE: - 15 W	
Maximum power consumption in W	6 W typical	
Standby consumption	< 0.5 W	
Display resolution	1280 x 800 pixels	
Brightness	300 cd/m²	
View angle horiz x vert	170° horizontal 170° vertical	
Communication port protocol	Ethernet	
Port Ethernet	10/100BASE	
Integrated connection type	Ethernet port USB port HDMI Micro SD card port Audio output	
Connector type	Power input	
Contrast ratio	800:1	
Aspect ratio	16:9	
Response time	30 ms typical	
Mounting location	Wall mounting	
Device mounting	Flush Surface	
Width	Cover frame: 316 mm	
Height	Cover frame: 220 mm	
Depth	Cover frame: 6 mm	

Cover frame colour tint

Environment

Ambient air temperature for operation	040 °C	
Relative humidity	1085 %	
Standards	IEEE 802.3af	

Packing Units

WEEE

Packing Units		
Unit Type of Package 1	PCE	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☐ End Of Life Information	

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Life Is On | IICLIPSAL