

Product data sheet Characteristics

5750WPL-GY

C-BUS - occupancy sensor - IP66 - infrascan learn enabled



Main Range C-Bus Clipsal Product brand Product or component Occupancy sensor type Device application Lighting Sensor type PIR Product specific Staircase monitoring application

Grey

Complementary

[Ue] rated operational voltage	1536 V DC
[In] rated current	18 mA
Communication network type	C-Bus 100
Number of channels	1
Type of setting	Light sensitivity adjustable
Light intensity adjustment	1 lux user selectable
Data backed up	Non-volatile memory
Local signalling	LEDstatus:
Timer resolution	1 s
Warm-up time	5 s
Horizontal detection angle	0110 °
Time delay range	01 s (switch-on)
Duty cycle	1090 min
Detection face	Lateral: 12 m
	Frontal: 18 m
C Bus termination	2 flying leads
Material	Plastic
Device mounting	Surface
Mounting support	Wall
	Ceiling
Mounting height	2.4 m
Fixing center	84 mm
Width	74 mm
Height	111 mm
Depth	138 mm
Colour code	GY

Colour

Environment

IP degree of protection	IP66
Ambient air temperature for operation	045 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	340 g	
Package 1 Height	12.6 cm	
Package 1 width	17.6 cm	
Package 1 Length	24.8 cm	

Offer Sustainability

EU RoHS Directive	Under investigation
Circularity Profile	End Of Life Information

Life Is On