

Product data sheet Characteristics

L5504D2A 4 CHANNEL DIMMER DIN LEARN



Main Range C-Bus Product brand Clipsal Product or component Dimmer Device application Control Device presentation Basic element Load type Inductive

Complementary

- Complementary		
[Ue] rated operational voltage	220240 V AC	
Network frequency	4753 Hz	
Nominal output power	460 W	
Number of modules	12	
Local signalling	LED	
Number of channels	4	
Mounting support	DIN rail	
Size	Base: 215 x 85 x 65 mm	

Environment

IP degree of protection	IP20	

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	769 g	
Package 1 Height	9.7 cm	
Package 1 width	10.7 cm	
Package 1 Length	22.5 cm	

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.