

CANDLE HALOGEN GLOBES

- Input voltage: 240V AC
- Wattage: 18W & 28W
- Clear or frosted glass
- 30% more energy saving compared to incandescent
- Especially suitable for chandeliers and small fittings
- Can be used indoors & outdoors in a waterproof fitting
- Suitable for dimming

2,000
HRS

1 YEAR
WARRANTY

DIMMABLE



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	DIAM (mm)	CARTON QTY
CLEAR								
CLAHACAN18WBCCL	18W CAN HALOGEN BC CLEAR	B22	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WBCCL	28W CAN HALOGEN BC CLEAR	B22	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WESCL	18W CAN HALOGEN ES CLEAR	E27	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WESCL	28W CAN HALOGEN ES CLEAR	E27	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WSBCCL	18W CAN HALOGEN SBC CLEAR	B15	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WSBCCL	28W CAN HALOGEN SBC CLEAR	B15	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WSESCL	18W CAN HALOGEN SES CLEAR	E14	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WSESCL	28W CAN HALOGEN SES CLEAR	E14	2800	370	28=40	95	Ø35	10/100
FROSTED								
CLAHACAN18WBCFR	18W CAN HALOGEN BC FROSTED	B22	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WBCFR	28W CAN HALOGEN BC FROSTED	B22	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WESFR	18W CAN HALOGEN ES FROSTED	E27	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WESFR	28W CAN HALOGEN ES FROSTED	E27	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WSBCFR	18W CAN HALOGEN SBC FROSTED	B15	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WSBCFR	28W CAN HALOGEN SBC FROSTED	B15	2800	370	28=40	95	Ø35	10/100
CLAHACAN18WSESFR	18W CAN HALOGEN SES FROSTED	E14	2800	210	18=25	95	Ø35	10/100
CLAHACAN28WSESFR	28W CAN HALOGEN SES FROSTED	E14	2800	370	28=40	95	Ø35	10/100

Brochure updated on 13.12.2016