

29-31 Richland St. Kingsgrove. Sydney NSW 2208 Australia

Phone: 02 9554 9600 | Fax: 02 9554 9433

enquiries@domuslighting.com.au | www.domuslighting.com.au

Date: 04/2019

Installation Manual

DEEP-10

Variants		Itam Na	Colour Toron	
Blk	Wht	Item No.	Colour Temp	
20667	20670	DEEP-10-WW	3000K Warm White	
20668	20671	DEEP-10-NW	4000K Neutral White	
20669	20672	DEEP-10-W	5000K White	

Description: Deepset LED Downlight


Thank you for purchasing your new DEEP-10 downlight, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

Specifications

-1								
Voltage:	240V AC	Lumen (±5%):	Warm White 3000K - 767lm Neutral White 4000K - 833lm White 5000K - 900lm	Dimmable:	Yes			
Power:	10W	Beam Angle:	36°	Operating Temp:	-20°C~45°C			
IP Rating:	IP40	CCT:	3000K - 4000K - 5000K					
CRI:	≥80	Lifespan:	50,000Hrs					


Step 1

Open a hole according to the cutout size of led downlight.




Step 2

Use screw-driver to open the driver terminal cover, feed the main AC wire LN in terminal block respectivley, then fix the cover back,




Step 3

Connect the downlight with driver, hold back the spring clip the push the downlight into the hole.



Connect the downlight with driver, hold back the spring clip then push the downlight into the hole.



Note: -The lamp must be installed by professional electrician

-Ensure the power supply is switched off before fitting this product

-Do not touch the lamp when in use

-Keep away from hot steam and corrosive gas