

GLS HALOGEN GLOBES

- Input voltage: 240V AC
- Wattage: 18W, 28W, 42W, 53W & 72W
- 30% more energy saving compared to incandescent
- Clear or frosted glass
- Suitable for dimming



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	DIAM (mm)	CARTON QTY
CLEAR BC								
CLAHAGLS18WBCCL	18W GLS HALOGEN BC CL	B22	2800	210	18=25	103	Ø55	10/100
CLAHAGLS28WBCCL	28W GLS HALOGEN BC CL	B22	2800	370	28=40	103	Ø55	10/100
CLAHAGLS42WBCCL	42W GLS HALOGEN BC CL	B22	2800	630	42=60	103	Ø55	10/100
CLAHAGLS53WBCCL	53W GLS HALOGEN BC CL	B22	2800	840	53=75	103	Ø55	10/100
CLAHAGLS72WBCCL	72W GLS HALOGEN BC CL	B22	2800	1220	72=100	103	Ø55	10/100
CLEAR ES								
CLAHAGLS18WESCL	18W GLS HALOGEN ES CL	E27	2800	210	18=25	103	Ø55	10/100
CLAHAGLS28WESCL	28W GLS HALOGEN ES CL	E27	2800	370	28=40	103	Ø55	10/100
CLAHAGLS42WESCL	42W GLS HALOGEN ES CL	E27	2800	630	42=60	103	Ø55	10/100
CLAHAGLS53WESCL	53W GLS HALOGEN ES CL	E27	2800	840	53=75	103	Ø55	10/100
CLAHAGLS72WESCL	72W GLS HALOGEN ES CL	E27	2800	1220	72=100	103	Ø55	10/100
FROSTED BC								
CLAHAGLS18WBCFR	18W GLS HALOGEN BC FR	B22	2800	210	18=25	103	Ø55	10/100
CLAHAGLS28WBCFR	28W GLS HALOGEN BC FR	B22	2800	370	28=40	103	Ø55	10/100
CLAHAGLS42WBCFR	42W GLS HALOGEN BC FR	B22	2800	630	42=60	103	Ø55	10/100
CLAHAGLS53WBCFR	53W GLS HALOGEN BC FR	B22	2800	840	53=75	103	Ø55	10/100
CLAHAGLS72WBCFR	72W GLS HALOGEN BC FR	B22	2800	1220	72=100	103	Ø55	10/100
FROSTED ES								
CLAHAGLS18WESFR	18W GLS HALOGEN ES FR	E27	2800	210	18=25	103	Ø55	10/100
CLAHAGLS28WESFR	28W GLS HALOGEN ES FR	E27	2800	370	28=40	103	Ø55	10/100
CLAHAGLS42WESFR	42W GLS HALOGEN ES FR	E27	2800	630	42=60	103	Ø55	10/100
CLAHAGLS53WESFR	53W GLS HALOGEN ES FR	E27	2800	840	53=75	103	Ø55	10/100
CLAHAGLS72WESFR	72W GLS HALOGEN ES FR	E27	2800	1220	72=100	103	Ø55	10/100

Brochure updated on 13.12.2016

