



Scan to explore
MDF6 online

Microled MDF6

5W Recessed Petite Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
MDF6	3 (3000K)	(CRI 90+ Standard)	MB (Medium)	W (White)	LT (Leading & Trailing Edge)
	4 (4000K)			B (Black)	DALI (DALI) 110V (1-10V)

Order Code **MDF64-MB-W-LT**





To configure this downlight, please visit
trendlighting.com.au/product/microled-MDF6

Physical Characteristics

Trim Colour	White Black
Dimensions	Ø75 x 65 (H) mm
Spring Height	20 mm
Cutout	Circular 58 mm
Weight	170 g

Dimensions (mm)



Product Features

- Recessed petite LED downlight, manufactured with an aluminium body and powder coat finish
- Small but mighty, making it an ideal lighting solution for areas that require minimalistic appeal
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes



Technical Characteristics

Based on MDF64-MB-W-LT

LED Power	5W
LED Type	COB
Lumen Output	585 lm
Luminous Flux	509 lm
Efficacy	80.79 lm/W
Colour Temperature	3000K 4000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L70)
Beam Angle	Medium

System Power	6.3W Typical
Driver Model	Trend 150211-160 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-42V DC 160mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge DALI 1-10V

General Characteristics

Category	Downlights
Family	Microled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP44



Scan to explore
MDF6 online

Microled MDF6

5W Recessed Petite Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
MDF6	3 (3000K)	(CRI 90+ Standard)	MB (Medium)	W (White)	LT (Leading & Trailing Edge) DALI (DALI) 110V (1-10V)
	4 (4000K)			B (Black)	

Order Code **MDF64-MB-W-LT**

To configure this downlight, please visit
trendlighting.com.au/product/microled-MDF6

Trim Colour



W
White Trim



B
Black Trim