



Scan to explore  
XDK10 online

# Miniled XDK10

10W Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XDK10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XDK104-WB-W-LT**



## Product Features

- Recessed LED downlight, designed to visually integrate into the ceiling while providing low glare and high lumen output
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

## Product Attributes




To configure this downlight, please visit  
[trendlighting.com.au/product/miniled-XDK10](http://trendlighting.com.au/product/miniled-XDK10)

## Physical Characteristics

Trim Colour	White   Black   Silver
Dimensions	Ø112 x 87 (H) mm
Spring Height	30 mm
Cutout	Circular 76-92 mm
Weight	250 g

## Dimensions (mm)




## Technical Characteristics

Based on XDK104-WB-W-LT

LED Power	10W
LED Type	COB
Lumen Output	1450 lm
Luminous Flux	1171 lm
Efficacy	100.09 lm/W
Colour Temperature	2700K   3000K   3500K   4000K
Colour Technology	CRI 90+   CRI 93+ VIVID   CRI 97+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L80)
Beam Angle	Narrow   Medium   Wide
System Power	11.7W Typical
Driver Model	Trend 150218-300 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge   DALI   1-10V

## General Characteristics

Category	Downlights
Family	Miniled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP44



Scan to explore  
XDK10 online

# Miniled XDK10


10W Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
<b>XDK10</b>	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XDK104-WB-W-LT**

To configure this downlight, please visit  
[trendlighting.com.au/product/miniled-XDK10](http://trendlighting.com.au/product/miniled-XDK10)


## Trim Colour



W  
**White Trim**



B  
**Black Trim**



S  
**Silver Trim**