DOMUS®

NC

UV/IF

LED

NEO-35 Downlight

Description

The NEO-35 is the third in the line-up of single point COB LED down lights. Features include deep set frame and glass diffuser with a choice of a black or satin white powder coated finish. Light is provided from a single point COB high performing LED with a perfectly matched 60° optical reflector. The reflector behaves in much the same way as a metal halide fixture does with the favourable scallop style illumination. Added benefits of an IP44 rating and fully mains dimmable LED driver makes this a perfect alternative to metal halide and PLC styled down lights. Applications include schools, shopping centres, retail shops etc.

Specification Features

Input Voltage:	240V AC		
Power (W):	35W		
IP rating (IP):	44*		
Lumens (lm):	Warm White 3000K - 3100lm		
	Neutral White 4000K - 3150lm		
	White 5000K - 3200lm		
LED type:	EPISTAR COB		
CCT:	3000К - 4000К - 5000К		
CRI:	≥80		
Beam angle (°):	60°		
Dimmable:	Yes**		
Lifespan (hrs):	50,000hrs		
Cutout (Ø):	Ø200-210mm		
IPart #:	01633S15-GAJEJB6		
* IP44 rating is from the underside of the down light once installed into the ceiling.			


** Tested on the Domus dimmer series. May work on other but not tested.



ies

3yr

Diagrams / Additional



Cutout: 200-210mm

Item No.	Variant	Colour
NEO-35-WHT	20580	Warm White
	20584	Neutral White
	20581	White
	20463	Warm White
NEO-35-BLK	20464	Neutral White
	20465	White

DOMUS®

NC

ŮV/ĨF

LED

NEO-25 Fixed LED Downlight

Description

The NEO-25 is the second in the line-up of single point COB LED down lights. Features include deep set frame and glass diffuser with a choice of a black or satin white powder coated finish. Light is provided from a single point COB high performing LED with a perfectly matched 60° optical reflector. The reflector behaves in much the same way as a metal halide fixture does with the favourable scallop style illumination. Added benefits of an IP44 rating and fully mains dimmable LED driver makes this a perfect alternative to metal halide and PLC styled down lights. Applications include schools, shopping centres, retail shops etc.

ies


3yr

Specification Features

Input Voltage:	240V AC			
Power (W):	25W			
IP rating (IP):	44*			
Lumens (lm):	Warm White 3000K - 2200lm Neutral White 4000K - 2250lm White 5000K - 2300lm			
LED type:	EPISTAR COB			
CCT:	3000К - 4000К - 5000К			
CRI:	≥80			
Beam angle (°):	60°			
Dimmable:	Yes**			
Lifespan (hrs):	50,000hrs			
Cutout (Ø):	Ø160-170mm			
IPart #:	01633S15-GAJEJB6			
* IP44 rating is from the underside of the down light once installed into the ce				

IP44 rating is from the underside of the down light once installed into the ceiling.
 ** Tested on the Domus dimmer series. May work on others but not tested.

Diagrams / Additional



Cutout: 160-170mm

Item No.	Variant	Colour
	20578	Warm White
NEO-25-WHT	20583	Neutral White
	20579	White
	20460	Warm White
NEO-25-BLK	20461	Neutral White
	20462	White

DOMUS®

NO UV/IR

NEO-13 Fixed LED Downlight

Description

The NEO-13 is the first in the line-up of single point COB LED down lights. Features include deep set frame and glass diffuser with of black or satin white powder coated finish. Light is provided from a single point COB high performing LED with a perfectly matched 60° optical reflector. The reflector behaves in much the same way as a standard 50W halogen lamp does with the favourable scallop style illumination. Added benefits of an IP44 rating and fully mains dimmable LED driver makes this a perfect alternative to halogen and CFL style down lights.




LED

ies

3yr


Specification Features

Input Volta	e: 240V AC		
Power (W):	13W		
IP rating (IP	44*		
Lumens (Im	: Warm White 3000K - 850lm		
	Neutral White 4000K - 880lm		
	White 5000K - 900lm		
LED type:	EPISTAR COB		
CCT:	3000К - 4000К - 5000К		
CRI:	≥80		
Beam angle	(°): 60°		
Dimmable:	Yes**		
Lifespan (hi): 50,000hrs		
Cutout (Ø):	Ø90mm		
IPart #:	01633S15-GAJEJB6		
* IP44 rating is from the underside of the down light once installed into the ceiling.			





Diagrams / Additional



 20576
 Warm White

 NEO-13-WHT
 20582
 Neutral White

 20577
 White

 20457
 Warm White

 20457
 Warm White

 20457
 Warm White

 20457
 Warm White

 20458
 Neutral White

 20458
 Neutral White

 20459
 White

Item No.

Variant

Colour

Cutout: 90mm