NO UV/IR



Neo-Pro-13 LED Recessed Downlight

Description

The NEO-PRO range of LED downlights are the latest upgrade to the NEO Series, with improved functions such as TRIO Tri-colour switchable technology as well as a higher IP Rating for wet areas. Designed to reduce glare as well as maintaining high performance in light output and energy consumption. LED recessed downlight with anti-glare deep set frame, frosted diffuser, and an integrated dimmable LED driver with flex & plug. Fully dimmable with suitable dimmers.

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.



ies

65


LED

3yr


Specification Features

Input Voltage:	240V			
Power (W):	13			
IP rating (IP):	IP65**			
Lumens (lm):	Warm White 3000K - 850lm			
	Neutral White 4000K - 1000lm			
	White 5700K - 900lm			
LED type:	SMD			
CCT:	3000K - 4000K - 5700K			
CRI:	≤90			
Beam angle (°):	80°			
Dimmable:	Yes*			
Lifespan (hrs):	50,000hrs			
Cutout (Ø):	Ø90mm			
*Fully dimmable with suitable dimmers.				
**IP65 from front only.				

Diagrams / Additional



Cutout: Ø90-95mm





Item No.	Variant		ССТ
item No.	Wht	Blk	CCI
	20916	20915	TRIO
NEO-PRO-13-REC	DALI		
	21607	21608	TRIO

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.