


PDL SERIES

LED EXTERIOR SURFACE MOUNTED WALL/STEP LIGHTS

- Input voltage: 12V DC
- Nominal current: 150mA
- LED chips: 2835 LED
- Ambient temperature: -40 to 85°C



Part No.	PDL1SQBRZ
Description	PILLAR LED 1 WAY Square Bronze
Material	Bronze
Wattage	3W
Kelvin	3000K
Lumens	300lm
CRI	75
Weight	0.62kg
Box	10x10x3.5cm
Carton QTY	1/20



Part No.	PDLUDRECTBRZ
Description	PILLAR LED UP/DN RECT Bronze
Material	Bronze
Wattage	2X3W
Kelvin	3000K
Lumens	2X300lm
CRI	75
Weight	1.08kg
Box	19.8x9.5x3.5cm
Carton QTY	1/20



Part No.	PDL1SQSS
Description	PILLAR LED 1 WAY Square SS
Material	316 Stainless Steel
Wattage	3W
Kelvin	3000K
Lumens	300lm
CRI	75
Weight	0.58kg
Box	10x10x3.5cm
Carton QTY	1/20



Part No.	PDLUDRECTSS
Description	PILLAR LED UP/DN RECT SS
Material	316 stainless steel
Wattage	2X3W
Kelvin	3000K
Lumens	2X300lm
CRI	75
Weight	0.94kg
Box	19.8x9.5x3.5cm
Carton QTY	1/20



Part No.	PDL1SQBL
Description	PILLAR LED 1 WAY Square Black
Material	Aluminium
Wattage	3W
Kelvin	3000K
Lumens	300lm
CRI	75
Weight	0.19kg
Box	10x10x3.5cm
Carton QTY	1/20



Part No.	PDLUDRECTBLK
Description	PILLAR LED UP/DN RECT Matte Black
Material	Aluminium
Wattage	2X3W
Kelvin	3000K
Lumens	2X300lm
CRI	75
Weight	0.5kg
Box	20x12x5cm
Carton QTY	1/25

RECOMMENDED DRIVERS: All CLA 12V DC Constant voltage drivers

PART NO.	MIN. LOAD	MAX. LOAD	PDLUDRECT (6W)	PDL1SQ (3W)
DRIV1	1.2W	9.6W	1PC / DRIVER	1-3PCS / DRIVER
OTTER1	1.2W	9.6W	1PC / DRIVER	1-3PCS / DRIVER
CLA111011	1W	8W	1PC / DRIVER	1-2PCS / DRIVER
CLA113011	3W	24W	4PCS / DRIVER	1-8PCS / DRIVER

