

Resiled RDF8

8W IP65 Rated Recessed Downlight



Scan to explore RDF8 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
RDF8	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)	LT (Leading & Trailing Edge)
	4 (4000K)			B (Black)	DALI (DALI)
				S (Silver)	110V (1-10V)

Order Code RDF84-WB-W-LT




To configure this downlight, please visit trendlighting.com.au/product/resiled-RDF8

Physical Characteristics

Trim Colour	White Black Silver
Dimensions	Ø110 x 65 (H) mm
Spring Height	15 mm
Cutout	Circular 76-92 mm
Weight	230 g

Dimensions (mm)





Product Features

- Recessed LED downlight with sealed body providing an IP65 rating, manufactured with an aluminium body and powder coat finish
- Covering 76 to 92 mm cutout sizes, an ideal replacement for existing downlights
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes













Technical Characteristics	Based on RDF84-WB-W-LT			
LED Power	8.5W			
LED Type	COB			
Lumen Output	1050 lm			
Luminous Flux	955 lm			
Efficacy	88.43 lm/W			
Colour Temperature	3000K 4000K			
Colour Technology	CRI 90+			
Colour Deviation	SDCM ≤ 3			
Lifetime	50,000 hours (L70)			
Beam Angle	Wide			
System Power	10.8W Typical			
Driver Model	Trend 150208-250 (L&T)			
Input	180-265V AC 50/60 Hz			
Output	30-40V DC 250mA			
Power Factor	>0.93			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Leading & Trailing Edge DALI 1-10V			

General Characteristics

Downlights
Resiled
Ceiling
Recessed
IC-4
IP65



Resiled RDF8



8W IP65 Rated Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
RDF8	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)	LT (Leading & Trailing Edge)
	4 (4000K)			B (Black) S (Silver)	DALI (DALI) 110V (1-10V)

Order Code RDF84-WB-W-LT

To configure this downlight, please visit

trendlighting.com.au/product/resiled-RDF8

Trim Colour







White Trim

Black Trim

S Silver Trim