DOMU

enquiries@domuslighting.com | www.domuslighting.com

Installation Manual

Date: 05/2018

STAD DD 180


SIAK-FD-IOU					
Variant	Item No.	Description			
21065		10W LED Pendant Light, 3000K Warm White. Black Finish			
21066	STAR-PD-10W-180-BLK	10W LED Pendant Light, 4000K Neutral White. Black Finish			
21067		10W LED Pendant Light, 5000K White. Black Finish			
21068		10W LED Pendant Light, 3000K Warm White. Satin White Finish			
21069	STAR-PD-10W-180-WHT	10W LED Pendant Light, 4000K Neutral White. Satin White Finish			
21070		10W LED Pendant Light, 5000K White. Satin White Finish			

Thank you for purchasing your new LED STAR-PD-180, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.


Specifications

Voltage:	240V	Lumen (±5%):	Warm White 3000K - 1000lm Neutral White 4000K -1050lm White 5000K - 1100lm	Dimmable:	NO
Power:	10W	Beam Angle:	60°	Operating Temp:	-20°C~45°C
IP Rating:	IP20	CCT:	3000K - 4000K - 5000K	Power Factor:	0.8
CRI:	≥80	Lifespan:	50,000hrs		


1. Take out the accessories from the accessory box



 \Rightarrow




4. Properly align the mounting holes between back plate and mounting bracket, corresponding polarities between the wires on



3. Take lamp out of the box, connet the

the ceiling and terminal by screwdriver.



then lock them together with screw,

Note: -The lamp must be installed by professional electrician -Ensure the power supply is switched off before fitting this product -Do not touch the lamp when in use -Keep away from hot steam and corrosive gas