

Push button inteface, C-Bus, 40 Series module, master

5041NMML

Range	C-Bus
Product brand	Clipsal
Product name	Series 40M
Product or component type	Push-button interface
Device application	Control
Colour	Transparent green
Switch application	Load switching Dimming up/down control Timer Scene control Bell switch Shutter control Fan speed control Blind control

Complementary

o impromortary	
Range compatibility	C-Bus Iconic wall plate Pro Series wall plate
Dimmer control	255 possible levels
Device mounting	Wall mounted by Series 40M grid
[Ue] rated operational voltage	1536 V DC
Input impedance	100 kOhm at 1 kHz
Local signalling	LED (red/blue) for status
Suitable cable type	Twisted unshielded pairs cable category 5e
Isolation voltage	3.75 kV from C-Bus to mains
Communication network type	C-Bus
Module type	Master
Control type	Push-button
Depth	36 mm
Width	22.8 mm
Height	22.8 mm
Net weight	0.013 kg
Material	Plastic

5 s
Programmed with learn mode Programmed with C-Bus software
1s18h12m15s
18 mA

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 % non-condensing
Product certifications	RCM
Standards	AS/NZS CISPR 15 AS/NZS CISPR 14-1 AS/NZS 60669.2.1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	55.0 g
Package 1 Height	2.7 cm
Package 1 width	2.7 cm
Package 1 Length	5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information