



BOLLARD FLAT SL7088FC TC - 10W

Flat profile, IP65 circular bollard, integral LED control gear with selectable CCT

Application

Ideal for residential or apartment exterior pathways

Design Specifications

- Die-cast aluminium body, flat profile design, base plate mounting, rag bolts included
- Durable BLACK powder coated finish
- Clear polycarbonate lens
- High efficiency LED optics
- Integral LED control gear, IP65, IK08 performance
- SL7088DC50TC - 120mm Ø, 640mm height
SL7088DC85TC - 120mm Ø, 990mm height

Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	SL7088FC50TC/BK	240	10	725/760/740	3000/4000/5000	250
	SL7088FC85TC/BK	240	10	725/760/740	3000/4000/5000	250

Mass (kg)	Diameter (mm)	Dim (mm)	Body Colour
2.5	120	640(H)	BLACK
2.5	120	990(H)	BLACK

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

