



## CLARE S9062TC/S - 10W

Recessed LED downlight with sensor control and selectable colour temperature.

### Application

Ideal for interior service areas, bathrooms and storage spaces

### Design Specifications

- Selectable colour temperature with an integral DIP switch 3000K / 4000K / 5700K
- Integral PIR sensor control with a fixed 60 seconds ON motion detection function incorporating a light sensor function to engage when the lighting levels are <20lux
- Integral non-dimmable LED 10 watt control gear, IC - 4 rated.
- Designed with flex and plug for easy installation
- Stylish white trim and opal polycarbonate diffuser
- Cut - out 92mm



### Performance

In Built Sensor - **YES**  
Sensor Type - **PIR**

### Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	CRI
S9062TC/S	240	10	760/800/850	3000/4000/5700	90	80

Model No.	Body Colour	Cut Out (mm)	Dim (mm)
S9062TC/S	WHITE	92	115(W) x 73(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

### Dimensions


Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	Beam Angle (°)	CRI	CCT (K)	IP Rating	Max. Dim. (mm)	Dimension (mm)
S9062TC/S	240/250	10	760/800/850	90	80	3000/4000/5700	IP44	115(W) x 73(H)	Ø115

Power (W)	Input Voltage (V/AC)	Beam Angle (°)	Beam Spread (mm)	Working Temperature (°C)	Time to Start (s)	Light Control (m)	Installation Height (m)	Sensor Type
10	240/250	90	115	0-35	30	20	2.5	PIR

\*It will turn off in 30 seconds if there is no motion detected.


S9062TC-S CUT - OUT 92mm





## Photometric Data

Unit: cd C0/C180 — C90/C270 —



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY  
MATCH THE  
ECO GEM SFI  
DOWNLIGHT  
WITH THIS  
SDD400SFI  
DIMMER.**



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

