



COOLUM PLUS flickerGUARD S9068TC/FG - 9W

9 watt dimmable LED downlight, UGR<19, with selectable CCT and flickerGUARD

Application

Ideal for any residential or commercial interior space, experiencing nuisance harmonic induced flicker

Design Specifications

- The innovative flickerGUARD Coolum responds to both visual and non-visual harmonic induced flicker.
- Integral flickerGUARD trailing edge dimmable LED driver, with smooth dimming performance and flex and plug
- High efficiency LED optics, multi-faceted optical system, 60° beam distribution, UGR<19, CRI>90
- Selectable CCT 3000 / 4000 / 5700K
- White or black polyamide trim and body
- IC - 4 rated, double insulated



Performance

- Dimmable - YES



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9068TC/WH/FG	240	9	700/780/750	3000/4000/5700	60
	S9068TC/BK/FG	240	9	570/630/610	3000/4000/5700	60


Dimmable	CRI	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	90	92	103	89(H)
YES	90	92	103	89(H)



Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

Dimensions





Before selecting a downlight look out for the marks of Compliance and Safety. Starting with the RCM mark, this signals that the product has been tested to all relevant Australian Safety standards, to ensure the product delivers its designed safety performance. In addition and when thermal insulation batts are installed in the ceiling cavity, look out of the IC rating to ensure the product is suitable for such an application.

