





DIGITAL DIMMER - MASTER SDD350UM

MASTER - universal digital dimmer

Application

Smart lighting controls for residential and commercial applications

Design Specifications

- Push button control for trailing or leading edge dimming, with soft start and soft off technology
- Colour temperature selection functionality is achieved when used with compatible SAL downlights (S9842CS/WH)
- Multiple-location dimming by connecting SDD350UM with any number of secondary dimmers SDD300US can be achieved.
- Fit most popular switch plates, three complimentary mech caps provided, overheating and over current protection, full short circuit protection
- Programmable minimum brightness level and memory function, compliant to AS/NZS60669.2.1
- Supports ceiling sweep & exhaust fan < 60watt loads in leading edge mode only.





- Dimmable YES
- Dimmer Type Trailing & Leading edge

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Dim (mm)	Body Colour
	SDD350UM	240	300	44(L) x 23(W) x 23(H)	WHITE

Minimum load - 5 watt


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".






Dimensions

Dimensions



Wiring Diagram





S

.

272

70mm CUT OUT

For more information please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

© Copyright SAL - All Rights Reserved