





FLEXI STREAMLINE 12V SINGLE COLOUR WHITE 50M ROLL FLB1208/S50M - 8W/M

Versatile, CRI>90, COB LED single colour white, 50M roll, maximum run length 5M, IP44, strip width 8mm.

Application

Ideal for residential or commercial features

Design Specifications

- 50 metre roll with adhesive tape, 5 metre run length, cuttable every 36mm
- Beam distribution 140°, choice of 3000/4000/6000K
- Streamline COB LED chip technology, providing a smooth lighting profile
- Dimming options: (quick link)

Type A - Trailing edge dimming,

Type B - LED strip controller LT8915DIM/BT with LT8914DIM/RP if required,

Type C - Analogue 1-10V

Type D - DALI 2 control

- Heat sink required for system performance, LED channel options refer this section
- 12V constant voltage driver required, refer driver options

Performance

- Dimmable YES
- Dimmer Type REFER DIMMING OPTIONS

























Technical Specification

Product	Model No.	Input Voltage (V/DC)	Watts per metre (W/m)	Beam Angle (°)	CRI	Luminous Flux Per Meter (lm/m)
	FLB1208WW/S	12	8	140	90	500
	FLB1208CW/S	12	8	140	90	530
	FLB1208DL/S	12	8	140	90	560

LEDs Per Metre	Cutting Interval	Colour Temp. (K)	Body Colour	Dim (mm)
252	36	3000	CLEAR	1000(L) x 8(W) x 2(H)
252	36	4000	CLEAR	1000(L) x 8(W) x 2(H)
252	36	6000	CLEAR	1000(L) x 8(W) x 2(H)

NOTE: code displayed are per M

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



What is the importance of EMC? Electromagnetic Compatibility, defines the use of different electronic devices (such as electrical appliances, medical equipment, IEDs and driversetc) to operate without interference with other devices. This is a mandatory label (and testing) requirement for Australian Lighting equipment covered by AS/NZS CISPR 15. ACMA also recognises equivalent standards CISPR 15 and EN 55015.

If you are unsure, ask your supplier for EMC compliance.