





### **GEO S9345** - 32W

32 watt, LED inground IP67 luminaire, IK09 rated

## **Application**

Decorative accent solution, ideal for gardens and decorative pathways

## **Design Specifications**

- 316L stainless steel face cover, die-cast aluminium body
- Clear tempered glass diffuser, High performance multifaceted reflector
- Integral constant current non-dimmable LED driver
- IP68 PG11 PVC cable gland, silicon gasket, PVC installation canister included
- 450 mm 3 core rubber flex, Maximum load capacity 5000 kg



















# **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	S9345WW	240	32	2000	3000	80
	S9345CW	240	32	2000	4000	80

Beam Angle (°)	Diameter (mm)	Dim (mm)	Body Colour
24	250	220(L) x 250(W)	STAINLESS STEEL
24	250	220(L) x 250(W)	STAINLESS STEEL

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





## **Dimensions**

#### S9345







Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

For more information please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999

VIC/TAS/SA/NT: 03 9532 3168

WA: 08 9248 7458

