



LED GX53

GX53 base LED

Application

Perfect for under shelf feature lighting

Design Specifications

- Frosted glass diffuser
- Poly covered aluminium body
- High efficiency SMD LED
- Integral non-dimmable driver
- Double insulated class II
- Choice of 3000K/4000K/6000K, CRI>80



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
GX53/450WW	LED 5W3000K 420LM	240	5	420	3000	80
GX53/450CW	LED 5W 4000K 430LM	240	5	430	4000	80
GX53/450DL	LED 5W 6000K 450LM	240	5	450	6000	80

Model No.	Beam Angle (°)	Dimmable	Base Type
GX53/450WW	120	NO	GX53
GX53/450CW	120	NO	GX53
GX53/450DL	120	NO	GX53

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

