



LED STD25 NT

LED tube surface mount diffused linear batten

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish
- High efficiency LED T8 tubes ordered separately with a choice of 3000K / 4000K / 6000K, CRI>80
- Large terminal block, easy installation
- Safety HRC fuse installed
- High performance PMMA prism diffuser, beam distribution 120 degree
- Emergency and sensor options available



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Beam Angle (°)	Dimensions (mm)	Body Colour
STD25/106NT	LED DIFFUSED BATTEN 1 X 9W PROFILE NO TUBE	240	120	620(L) x 83(W) x 69(H)	WHITE
STD25/112NT	LED DIFFUSED BATTEN 1 X 18W PROFILE NO TUBE	240	120	1230(L) x 83(W) x 69(H)	WHITE
STD25/206NT	LED DIFFUSED BATTEN 2 X 9W PROFILE NO TUBE	240	120	620(L) x 83(W) x 109(H)	WHITE
STD25/212NT	LED DIFFUSED BATTEN 2 X 18W PROFILE NO TUBE	240	120	1230(L) x 83(W) x 109(H)	WHITE

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Photometric Data

Unit: cd C0/C180 _____ C90/C270 _____

STD25/212CW at 4000K

