



LED STD25EM - 18/36W

Wide body LED 18-36 watt surface mount diffused linear batten

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish
- High efficiency LED T8 tubes fitted, choice of 3000K, 4000K, 6000K, CRI>80
- Large terminal block, easy installation, safety fuse included
- High performance PMMA prism diffuser, beam distribution 120 degree
- Non maintained, independent emergency end cap, emergency with LiFePO4 battery included compliant to AS/NZS2293
- LED charge status display and test switch, guaranteed 90 minutes emergency function



Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	CRI	Beam Angle (°)	Body Colour	Dim (mm)
STD25/206EM	240	18	80	120	WHITE	630(L) x 109(W) x 83(H)
STD25/212EM	240	36	80	120	WHITE	1260(L) x 109(W) x 83(H)

Important notes: (1) Battery warranty twelve (12) months (2) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery MUST be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

**For more
information
please
scan me**

