





OPAL LGS8TC - 8W

8 watt LED GLS style opal lamps, with selectable CCT

Application

Energy efficient LED lamp solutions

Design Specifications

- Opal polycarbonate diffuser, beam distribution 200°
- Poly covered aluminium body, B22 and E27 lamp bases
- High efficiency LED optics, CRI>80
- Integral non-dimmable LED driver
- Selectable CCT 2700K/4000K/6000K
- 1:1 size to traditional GLS / A60 lamp, suits most GLS / A60 lamp fittings, double insulation

Performance

• Dimmable - NO























Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
0	LGS8TC/B22	240	8	700/750/700	2700/4000/6000	80
0	LGS8TC/E27	240	8	700/750/700	2700/4000/6000	80







Beam Angle (°)	Dimmable	Diameter (mm)	Length (mm)	Base Type
200	NO	60	112	B22
200	NO	60	112	E27

IMPORTANT, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions







THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE UNIFIT SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

