



PLUTO 30

Australian approved constant voltage LED drivers IP66

Application

Independent compact design

Design Specifications

- SELV and EMC compliant
- Safe no load operation, power factor 0.95, minimum load 1 watt
- 1.2M flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP66



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Dimensions (mm)
PLUTO 30/24V	LED DRIVER 24V 30W C-VOLT IP66	240	30	275(L) x 30(W) x 17(H)
PLUTO 30/12V	LED DRIVER 12V 30W C-VOLT IP66	240	30	275(L) x 30(W) x 17(H)
PLUTO 30/12V/NP	LED DRIVER 12V 30W C-VOLT IP66	240	30	275(L) x 30(W) x 17(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

PLUTO 30

