



## PLUTO DIM 1150 QP

Australian approved 1-10V dimmable constant current LED driver with selectable output

### Application

The perfect choice for constant current electronic lighting circuits

### Design Specifications

- SELV and EMC compliant, safe no load operation
- Compact design profile, electrical class II
- Overload and short circuit protection
- Dimmable 1-10V, dimming range 10%~100%
- Secondary output range 1150/1000/850/700mA
- Auxiliary 12V DC power source (maximum sink current 40mA)



### Performance

Dimmable - **YES**

Dimmer Type - **1-10V**

### Technical Specification

Model No.	Input Voltage (V/AC)	Frequency (Hz)	Power (W)	Output Current (mA)	Power Factor	Dim (mm)
PLUTO 1150/60QP/A	240	50	60	1150	0.9	180(L) x 46(W) x 30(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

# THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE  
CONTROL WITH  
SFI FLICKER  
CONTROL  
TECHNOLOGY**  
when paired with  
**SAL SFI downlights**



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

