





REC-BUNKER SE7087L - 18W

Vandal resistant, IP54 LED bunker ceiling mount luminaire, IK10 rated

Application

A reliable solution for commercial utility spaces

Design Specifications

- Robust die-cast aluminium body, designed with 20mm conduit entry points
- Durable white powder coated finish
- Stainless steel allen screws
- High efficiency SMD LED chips, beam distribution 90 degree
- Integral non-dimmable LED driver
- UV stabilised opal polycarbonate diffuser, silicon gasket

Performance

- Dimmable OPTIONAL
- Dimmer Type TRAILING EDGE

















Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7087L	240	18	1450	4000	80


Beam Angle (°)	Body Colour	Dim (mm)
90	WHITE	323(L) x 101(W) x 94(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".






Dimensions



Photometric Data







PIXIE AMBIENCE, CHANGE YOUR COLOUR TO MATCH YOUR STYLE.

The innovative PIXIE AMBIENCE SWITCH PLATES have been designed with the end user and installer in mind, allowing you to change the colour face plate as fashion demands.

For more information please scan me





