



STARPAD II SE7071TC - 15/100W

15 -100 watt IP65 LED floodlight with integral selectable colour temperature

Application













A versatile floodlight solution for residential and commercial exterior spaces

Design Specifications

- Robust die-cast aluminium body, IK 07 rated
- Durable black, silver or white powder coated finish
- Textured stalinite diffuser, secured in a robust aluminium body profile with integral breather for optimum system performance
- High efficiency SMD LED chips, non-dimmable LED driver, CRI > 80, CCT selectable 3000, 4000 or 5000K
- High performance optical system, beam distribution 110 degree
- Fitted cable gland with 600 mm 3 core rubber flex (15-30 watt models), 800mm for (50-100 watt models)



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7071/15TC2BK	240	15	1575/1800/1650	3000/4000/5000	80
	SE7071/15TC2SL	240	15	1575/1800/1650	3000/4000/5000	80
	SE7071/15TC2WH	240	15	1575/1800/1650	3000/4000/5000	80
	SE7071/30TC2BK	240	30	3150/3600/3300	3000/4000/5000	80
	SE7071/30TC2SL	240	30	3150/3600/3300	3000/4000/5000	80
	SE7071/30TC2WH	240	30	3150/3600/3300	3000/4000/5000	80
	SE7071/50TC2BK	240	50	5250/6000/5500	3000/4000/5000	80
	SE7071/50TC2SL	240	50	5250/6000/5500	3000/4000/5000	80
	SE7071/50TC2WH	240	50	5250/6000/5500	3000/4000/5000	80
	SE7071/100TC2/BK	240	100	10500/12000/11000	3000/4000/5000	80
	SE7071/100TC2/SL	240	100	10500/12000/11000	3000/4000/5000	80
	SE7071/100TC2/WH	240	100	10500/12000/11000	3000/4000/5000	80

Beam Angle (°)	Body Colour	Dim (mm)	Mass (kg)
110	BLACK	153(W) x 99(H) x 36(D)	0.54
110	SILVER	153(W) x 99(H) x 36(D)	0.54
110	WHITE	153(W) x 99(H) x 36(D)	0.54
110	BLACK	207(W) x 135(H) x 36(D)	0.84
110	SILVER	207(W) x 135(H) x 36(D)	0.84
110	WHITE	207(W) x 135(H) x 36(D)	0.84
110	BLACK	261(W) x 171(H) x 39(D)	1.25
110	SILVER	261(W) x 171(H) x 39(D)	1.25
110	WHITE	261(W) x 171(H) x 39(D)	1.25
110	BLACK	343(W) x 200(H) x 42(D)	2.45
110	SILVER	343(W) x 200(H) x 42(D)	2.45
110	WHITE	343(W) x 200(H) x 42(D)	2.45

NOTE: dimensions listed exclude trunnion assembly, refer to DIMENSION drawings for details.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

