



## STD TC TUBELINE DIFFUSE - 9/36W

Conventional LED tube diffuse battens 9 - 36 watt

### Application

Conventional LED interior battens ideal for residential and commercial service spaces

### Design Specifications

- Pressed steel base with PVC body
- Large terminal block, easy installation
- High efficiency LED T8 tubes fitted, beam distribution 120°, CRI >80, with selectable CCT lamps included, 3000K/4000K/6000K
- Safety HRC fuse installed
- Emergency and sensor option available
- Wire guard (STG series) option available



### Performance



In Built Sensor - **OPTIONAL**

### Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CRI	Beam Angle (°)	Dimmable
STD/106TC	240	9	650/750/700	80	120	NO
STD/112TC	240	18	1300/1500/1400	80	120	NO
STD/206TC	240	18	1300/1500/1400	80	120	NO
STD/212TC	240	36	2600/3000/2800	80	120	NO

Model No.	Dim (mm)	Body Colour
STD/106TC	625(L) x 65(W) x 77(H)	WHITE
STD/112TC	1225(L) x 65(W) x 77(H)	WHITE
STD/206TC	625(L) x 110(W) x 77(H)	WHITE
STD/212TC	1225(L) x 110(W) x 77(H)	WHITE

**IMPORTANT**, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



## Photometric Data

Unit: cd C0/C180 — C90/C270 —

STD/212TC at 4000K



# THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more  
information  
please  
scan me

