





STEIN SE7148 - 32W

IP65 LED architectural wall luminaire - up and down

Application

A decorative residential / commercial exterior or interior solution

Design Specifications

- Die-cast aluminium body and powder coated body profile
- Clear tempered glass cover
- High efficiency LED optics
- High performance multifaceted reflector system, standard beam distribution 25°, narrow beam distribution < 25° available
- Integral non-dimmable LED driver

Performance

• Dimmable - NO



























Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7148WW/BK	240	32	1600	3000	80
	SE7148WW/CB	240	32	1600	3000	80
	SE7148CW/BK	240	32	1600	4000	80
	SE7148CW/CB	240	32	1600	4000	80
	SE7148NB/WW/BK	240	32	800/500	3000	80
	SE7148NB/WW/CB	240	32	800/500	3000	80
	SE7148NB/CW/BK	240	32	800/500	4000	80
	SE7148NB/CW/CB	240	32	800/500	4000	80


Beam Angle (°)	Dim (mm)	Body Colour
25	234(W) x 286(H)	BLACK
25	234(W) x 286(H)	CHARCOAL BLACK
25	234(W) x 286(H)	BLACK
25	234(W) x 286(H)	CHARCOAL BLACK
25	234(W) x 286(H)	BLACK
25	234(W) x 286(H)	CHARCOAL BLACK
25	234(W) x 286(H)	BLACK
25	234(W) x 286(H)	CHARCOAL BLACK

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".






Dimensions



Photometric Data







Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

For more information please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999

VIC/TAS/SA/NT: 03 9532 3168

WA: 08 9248 7458

