



240V 50Hz	8W TOTAL WATTAGE	6W NON-MTD LAMP	SMD LED		CRI >80	Ta 40°C	D40	AS/NZS APPROVED
--------------	------------------------	-----------------------	---------	--	------------	------------	-----	--------------------

6W Pathfinder Emergency downlight is a general purpose, non-maintained LED emergency luminaire with IP65 weatherproof rating, compliant to AS/NZS2293.

The Pathfinder luminaire incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages

### FEATURES

- Compliant to AS/NZS 2293
- IP65 rating
- Energy efficient high output 6 watt LED
- 2-Pin flex & plug included
- Ceiling surface mount
- Injection moulded polycarbonate housing
- D40/D40 classification
- High density storage LiCoO2 batteries
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

### APPLICATIONS

Wet rooms, commercial and interior applications, coastal environment, apartments, shopping centres, hospitality, prisons and hospitals.

### CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres									
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0	
C0	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1	
C90	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1	

MODEL NO.	MOUNT TYPE	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR
20217/..	SURFACE	6	/05-WHITE

