



## TRADEGEM S9141TC - 9W


Dimmable IP44, 9 watt LED downlight with selectable CCT

### Application

Ideal for any residential or commercial interior space

### Design Specifications

- Selectable CCT 3000K/4000K/5700K
- Durable die-cast aluminium body profile, IC - 4 rated
- Stylish white powder coat finish, with optional colour trims available; satin nickel (S9141SN/RING), black (S9141BK/RING)
- Opal polycarbonate diffuser
- High efficiency LED optics
- Remote constant current trailing edge dimmable LED driver



### Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**




### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9141TC/WH	240	9	700/850/800	3000/4000/5700	110
Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	
YES	80	WHITE	92	104	26(H)	

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


## Dimensions



S9141TC



## Photometric Data

Unit: cd C0/C180 — C90/C270 —





Before selecting a downlight look out for the marks of Compliance and Safety. Starting with the RCM mark, this signals that the product has been tested to all relevant Australian Safety standards, to ensure the product delivers its designed safety performance. In addition and when thermal insulation batts are installed in the ceiling cavity, look out of the IC rating to ensure the product is suitable for such an application.

