



TUBELINE BARE STB - 18W

Conventional LED bare battens 18 watt

Application

Conventional designed LED surface mount battens, ideal for most commercial interior service spaces

Design Specifications

- Pressed steel base with PVC body dimensions
LWH: (2x9w) 625 x 100 x 77mm
- Large terminal block, easy installation, 2 x 9 watt models
- White powder coat finish
- High efficiency LED T8 tubes fitted, CRI > 80, CCT 4000K
- Safety fuse installed
- Optional models - wire guard (STG series) and emergency models with LiFePO4 battery technology compliant to AS/NZS2293 are available



Performance

- Dimmable - **NO**

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Lumens (lm)	CCT (K)	Power (W)	CRI
	STB/206 CW	240	1700	4000	18	80
	STB/206EM2500	240	1700	4000	18	80
	STB/212EM2500	240	3200	4000	36	80

Beam Angle (°)	Body Colour	Dim (mm)
120	WHITE	625(L) x 100(W) x 77(H)
120	WHITE	625(L) x 100(W) x 77(H)
120	WHITE	1225(L) x 100(W) x 77(H)

STB/206EM2500, STB/212EM2500 TUBELINE, Compliant to AS2293, LED charge status indicator, Test switch, Guaranteed 90 minutes emergency operation, Intelligent automatic recharging function, 16 hours charge time, Deep discharge protection, SELV compliant

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

**For more
information
please
scan me**

