



TUBULAR CLEAR LT25 - 2W

2 watt LED filament tubular lamp

Application

Energy efficient LED lamp solutions

Design Specifications

- Clear glass diffuser, E14 base, 240V
- High efficiency LED filament and colour rendering, CRI> 80
- Integral non-dimmable LED driver
- 320° beam angle
- Colour temperature 3000K
- Suitable to replace equivalent incandescent tubular lamp or pilot lamp, double insulation



100

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	ССТ (К)	CRI
LT25F830E14	LED FILAMENT T25 2W E14 3K	240	2	200	3000	80
Model No.	Beam Angle (°)	Dimmable	Dimensions (mm)		Base Type	
LT25F830E14	320	NO	84(L) x 25(W)		E14	

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



3000K



Dimensions

LT25F

