


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 64.61 lm/W			
MODEL		I <sub>max</sub> (cd)	97.11	S/MH(C0/180)	1.45
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.39
RATED VOLTAGE(V)		TOTAL FLUX(lm)	316.04	η UP,DN(C0-180)	0.3,45.3
NOMINAL FLUX(lm)	316.039	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.5,53.8
LAMPS INSIDE	1	η up(%)	0.8	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)		η down(%)	99.2	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### ZONAL FLUX DIAGRAM

#### ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	92.25	92.38	93.68	95.69	96.75	96.63	95.13	93.38	0- 10	9.062	9.062	2.87,2.87
20	87.30	87.50	89.98	93.81	96.10	96.11	93.18	89.66	10- 20	26.40	35.47	11.2,11.2
30	79.99	80.20	83.50	89.19	92.93	93.36	89.06	83.72	20- 30	41.29	76.75	24.3,24.3
40	69.78	69.86	73.77	80.98	86.11	87.56	82.13	75.12	30- 40	51.80	128.6	40.7,40.7
50	56.70	56.33	60.41	68.52	74.89	77.81	71.84	63.46	40- 50	56.05	184.6	58.4,58.4
60	41.42	40.02	43.77	51.93	59.31	63.68	58.01	48.96	50- 60	52.66	237.3	75.1,75.1
70	25.29	22.47	25.03	32.46	40.30	45.57	40.92	32.30	60- 70	41.65	278.9	88.3,88.3
80	11.22	7.832	7.874	13.49	19.94	25.32	21.90	15.62	70- 80	25.33	304.3	96.3,96.3
90	0.9971	0.5952	0.3659	0.9927	2.780	6.938	5.449	3.558	80- 90	9.104	313.4	99.2,99.2
100	0.1823	0.1974	0.1669	0.1822	0.1520	0.4693	0.2271	0.2276	90-100	1.049	314.4	99.5,99.5
110	0.2126	0.2579	0.2124	0.2127	0.2126	0.2125	0.2124	0.2431	100-110	0.2431	314.6	99.6,99.6
120	0.2430	0.2733	0.2275	0.2581	0.2126	0.2733	0.2731	0.3188	110-120	0.2541	314.9	99.6,99.6
130	0.3188	0.3186	0.3034	0.2581	0.3493	0.3342	0.3337	0.3796	120-130	0.2699	315.2	99.7,99.7
140	0.3492	0.3644	0.3188	0.3036	0.3647	0.3795	0.3794	0.4099	130-140	0.2624	315.4	99.8,99.8
150	0.4101	0.3947	0.3792	0.3340	0.4103	0.4099	0.4098	0.4403	140-150	0.2376	315.7	99.9,99.9
160	0.4253	0.4554	0.4246	0.3797	0.4408	0.4406	0.4553	0.4706	150-160	0.1917	315.9	99.9,99.9
170	0.4557	0.4858	0.4853	0.4555	0.4860	0.4858	0.5006	0.4858	160-170	0.1293	316.0	100,100
180	0.5012	0.5010	0.5006	0.5010	0.4860	0.5010	0.5158	0.4858	170-180	0.0460	316.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 156.51 lm

%lum = 49.5%

%lamp = 49.5%

Conical surface Flux(120deg): 237.27 lm

%lum = 75.1%


%lamp = 75.1%

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3204	1426
80	3231	2269
75	3432	3061
70	3696	3663
65	3940	4086
60	4141	4381
55	4297	4580
50	4409	4704
45	4495	4779


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz		
Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.01	1.01	1.01	.99
1.0	1.03	.98	.94	1.00	.96	.92	.96	.92	.89	.92	.89	.86	.88	.86	.84	.81
2.0	.89	.82	.76	.87	.80	.75	.83	.77	.73	.80	.75	.71	.76	.73	.69	.67
3.0	.77	.69	.62	.76	.68	.61	.73	.66	.60	.70	.64	.59	.67	.62	.58	.56
4.0	.68	.59	.52	.67	.58	.52	.64	.57	.51	.62	.55	.50	.59	.54	.49	.47
5.0	.61	.51	.45	.60	.51	.44	.57	.50	.44	.55	.48	.43	.53	.47	.43	.40
6.0	.54	.45	.39	.53	.45	.38	.52	.44	.38	.50	.43	.38	.48	.42	.37	.35
7.0	.49	.40	.34	.48	.40	.34	.47	.39	.33	.45	.38	.33	.44	.38	.33	.31
8.0	.45	.36	.30	.44	.36	.30	.43	.35	.30	.41	.34	.29	.40	.34	.29	.27
9.0	.41	.33	.27	.40	.32	.27	.39	.32	.27	.38	.31	.26	.37	.31	.26	.24
10.0	.38	.30	.24	.37	.29	.24	.36	.29	.24	.35	.29	.24	.34	.28	.24	.22



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### WEC AND CCEC

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz		
Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.330	.188	.059	.322	.184	.058	.309	.177	.057	.296	.171	.055	.284	.165	.053		
2.0	.306	.168	.051	.299	.165	.051	.287	.160	.050	.276	.155	.048	.265	.150	.047		
3.0	.281	.149	.045	.275	.147	.044	.264	.143	.044	.254	.139	.043	.245	.135	.042		
4.0	.258	.134	.039	.253	.132	.039	.243	.129	.038	.234	.126	.038	.226	.123	.037		
5.0	.237	.121	.035	.233	.119	.035	.224	.117	.034	.216	.114	.034	.209	.111	.033		
6.0	.219	.110	.031	.215	.109	.031	.208	.106	.031	.200	.104	.031	.194	.102	.030		
7.0	.204	.101	.029	.200	.100	.028	.193	.098	.028	.187	.096	.028	.181	.094	.028		
8.0	.190	.093	.026	.186	.092	.026	.180	.090	.026	.175	.088	.026	.169	.087	.025		
9.0	.177	.086	.024	.175	.085	.024	.169	.084	.024	.164	.082	.023	.159	.081	.023		
10.0	.167	.080	.022	.164	.079	.022	.159	.078	.022	.154	.077	.022	.150	.075	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.197	.197	.197	.168	.168	.168	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.188	.162	.139	.161	.139	.120	.110	.096	.083	.063	.056	.048	.020	.018	.016	
2.0	.181	.138	.103	.155	.119	.089	.106	.082	.062	.061	.048	.036	.020	.016	.012	
3.0	.173	.121	.079	.148	.104	.069	.102	.072	.048	.059	.042	.028	.019	.014	.009	
4.0	.166	.108	.064	.142	.093	.055	.098	.065	.039	.057	.038	.023	.018	.012	.008	
5.0	.158	.098	.053	.136	.084	.046	.094	.059	.032	.054	.035	.019	.017	.011	.006	
6.0	.151	.089	.045	.130	.077	.039	.089	.054	.028	.052	.032	.016	.017	.010	.005	
7.0	.144	.082	.039	.124	.071	.034	.086	.050	.024	.050	.029	.014	.016	.010	.005	
8.0	.137	.077	.035	.118	.066	.030	.082	.047	.022	.048	.028	.013	.015	.009	.004	
9.0	.131	.072	.031	.113	.062	.027	.078	.044	.020	.046	.026	.012	.015	.008	.004	
10.0	.125	.067	.029	.108	.059	.025	.075	.041	.018	.044	.024	.011	.014	.008	.004	

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz										
Lamp Flux:316.039x1 lm										
NAME: 02 RGB+CCT G					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 0.02*1			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.2	22.8	21.5	23.0	23.3	21.5	23.1	21.8	23.3	23.5
3H	22.7	24.1	23.0	24.4	24.6	22.8	24.3	23.2	24.5	24.8
4H	23.2	24.6	23.6	24.9	25.1	23.3	24.7	23.6	24.9	25.2
6H	23.7	25.0	24.0	25.2	25.5	23.5	24.8	23.9	25.1	25.4
8H	23.8	25.1	24.2	25.4	25.7	23.5	24.8	23.9	25.1	25.4
12H	23.9	25.1	24.3	25.5	25.8	23.5	24.7	23.9	25.1	25.4
4H 2H	21.8	23.2	22.1	23.4	23.7	22.0	23.4	22.3	23.6	23.9
3H	23.3	24.5	23.7	24.9	25.2	23.5	24.7	23.8	25.0	25.3
4H	24.0	25.1	24.4	25.4	25.8	24.0	25.1	24.4	25.4	25.8
6H	24.5	25.5	25.0	25.9	26.3	24.3	25.3	24.7	25.7	26.1
8H	24.8	25.7	25.2	26.1	26.5	24.4	25.3	24.8	25.7	26.1
12H	24.9	25.8	25.4	26.2	26.6	24.4	25.3	24.8	25.7	26.1
8H 4H	24.2	25.1	24.6	25.5	25.9	24.2	25.1	24.6	25.5	25.9
6H	24.8	25.6	25.3	26.0	26.5	24.6	25.3	25.0	25.8	26.2
8H	25.1	25.8	25.6	26.2	26.7	24.7	25.4	25.2	25.8	26.3
12H	25.4	26.0	25.9	26.4	26.9	24.7	25.3	25.2	25.8	26.3
12H 4H	24.1	25.0	24.6	25.4	25.8	24.2	25.0	24.6	25.4	25.8
6H	24.8	25.5	25.3	26.0	26.4	24.6	25.3	25.1	25.7	26.2
8H	25.2	25.8	25.7	26.2	26.7	24.7	25.3	25.2	25.8	26.3
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4				

CIE Pub.117, 316.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -4.0)  
Area: 0.02 m2

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:


```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:



**AAI Figure**

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




**Note:**The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JINZHI  
 Test Date:2021-07-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
 Humidity:65.0%  
 Test Distance:9.660m [K=1.0000]  
 Remarks:

ISOLUX DIAGRAM

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### LED Avg.L Report

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4937
L_0~180 (75) av	4624
L_0~180 (85) av	4498
L_90~270 (65) av	4989
L_90~270 (75) av	4570
L_90~270 (85) av	4401
L_45 (65) av	5011
L_45 (75) av	4644
L_45 (85) av	4732

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.001V I:0.2038A P:4.8914W PF:1.0000 Freq:0Hz Lamp Flux:316.039x1 lm		
NAME: 02 RGB+CCT G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4			
5	94.0	94.0	94.1	94.4	94.8	95.3	95.7	96.1	96.3	96.4	96.2	96.0	95.4	95.2	94.6	94.2			
10	92.2	92.2	92.4	93.0	93.7	94.6	95.7	96.2	96.8	97.0	96.6	96.1	95.1	94.4	93.4	92.7			
15	90.0	89.9	90.2	91.0	92.1	93.5	95.1	95.9	96.7	97.1	96.6	96.0	94.4	93.2	91.7	90.7			
20	87.3	87.1	87.5	88.5	90.0	91.8	93.8	95.0	96.1	96.8	96.1	95.2	93.2	91.5	89.7	88.2			
25	84.0	83.7	84.2	85.3	87.1	89.4	91.9	93.5	94.9	95.8	95.0	93.9	91.4	89.3	87.0	85.1			
30	80.0	79.7	80.2	81.5	83.5	86.3	89.2	91.2	92.9	94.0	93.4	91.9	89.1	86.5	83.7	81.4			
35	75.2	74.8	75.4	76.9	79.1	82.3	85.5	88.0	90.0	91.4	90.9	89.2	86.0	82.9	79.8	77.0			
40	69.8	69.2	69.9	71.4	73.8	77.3	81.0	83.7	86.1	87.8	87.6	85.7	82.1	78.7	75.1	71.9			
45	63.6	62.9	63.5	65.2	67.5	71.3	75.3	78.4	81.1	83.2	83.2	81.3	77.4	73.6	69.7	66.1			
50	56.7	55.9	56.3	58.0	60.4	64.3	68.5	71.9	74.9	77.4	77.8	75.8	71.8	67.8	63.5	59.5			
55	49.3	48.2	48.5	50.1	52.5	56.5	60.7	64.3	67.6	70.4	71.3	69.4	65.4	61.1	56.6	52.3			
60	41.4	40.0	40.0	41.4	43.8	47.7	51.9	55.6	59.3	62.3	63.7	61.9	58.0	53.5	49.0	44.5			
65	33.3	31.6	31.2	32.4	34.5	38.2	42.4	46.2	50.1	53.4	55.0	53.4	49.8	45.4	40.7	36.5			
70	25.3	23.5	22.5	23.3	25.0	28.6	32.5	36.5	40.3	43.7	45.6	44.2	40.9	36.6	32.3	28.3			
75	17.8	15.9	14.5	14.6	15.8	19.1	22.6	26.3	30.1	33.4	35.5	34.3	31.5	27.5	23.6	20.3			
80	11.2	9.45	7.83	7.26	7.87	10.3	13.5	16.3	19.9	23.1	25.3	24.4	21.9	18.5	15.6	13.2			
85	5.59	4.25	3.14	2.35	2.48	3.62	5.53	7.56	10.1	13.2	15.6	15.0	12.9	10.5	8.75	7.44			
90	1.00	0.97	0.60	0.24	0.37	0.38	0.99	1.90	2.78	5.27	6.94	6.78	5.45	4.34	3.56	2.61			
95	0.18	0.21	0.20	0.20	0.17	0.17	0.24	0.21	0.14	1.42	1.97	2.00	1.38	1.16	0.83	0.70			
100	0.18	0.24	0.20	0.24	0.17	0.21	0.18	0.20	0.15	0.55	0.47	0.52	0.29	0.29	0.23	0.30			
105	0.23	0.29	0.21	0.27	0.18	0.27	0.18	0.21	0.20	0.20	0.24	0.27	0.15	0.18	0.20	0.21			
110	0.21	0.32	0.26	0.32	0.21	0.29	0.21	0.26	0.21	0.20	0.21	0.21	0.21	0.18	0.24	0.21			
115	0.21	0.35	0.26	0.35	0.23	0.33	0.26	0.29	0.21	0.20	0.26	0.21	0.24	0.18	0.29	0.26			
120	0.24	0.38	0.27	0.38	0.23	0.33	0.26	0.32	0.21	0.21	0.27	0.21	0.27	0.24	0.32	0.24			
125	0.27	0.41	0.29	0.40	0.30	0.36	0.26	0.33	0.32	0.23	0.30	0.23	0.30	0.24	0.35	0.26			
130	0.32	0.43	0.32	0.41	0.30	0.40	0.26	0.38	0.35	0.23	0.33	0.23	0.33	0.24	0.38	0.27			
135	0.32	0.44	0.32	0.43	0.30	0.41	0.29	0.39	0.36	0.24	0.35	0.24	0.33	0.26	0.39	0.30			
140	0.35	0.44	0.36	0.44	0.32	0.43	0.30	0.41	0.36	0.27	0.38	0.26	0.38	0.29	0.41	0.30			
145	0.38	0.47	0.39	0.47	0.33	0.46	0.32	0.42	0.41	0.27	0.41	0.30	0.39	0.29	0.44	0.32			
150	0.41	0.49	0.39	0.47	0.38	0.46	0.33	0.44	0.41	0.30	0.41	0.30	0.41	0.32	0.44	0.35			
155	0.43	0.50	0.44	0.49	0.39	0.47	0.36	0.45	0.44	0.32	0.44	0.32	0.44	0.35	0.46	0.39			
160	0.43	0.50	0.46	0.50	0.42	0.47	0.38	0.45	0.44	0.36	0.44	0.35	0.46	0.38	0.47	0.42			
165	0.46	0.50	0.47	0.50	0.44	0.50	0.44	0.48	0.47	0.40	0.46	0.43	0.49	0.39	0.49	0.44			
170	0.46	0.50	0.49	0.50	0.49	0.50	0.46	0.51	0.49	0.43	0.49	0.44	0.50	0.43	0.49	0.47			
175	0.47	0.50	0.49	0.52	0.49	0.50	0.49	0.49	0.50	0.46	0.49	0.46	0.52	0.46	0.49	0.48			
180	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.49	0.50	0.50	0.49	0.52	0.49	0.49	0.50			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks: