


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 53.23 lm/W			
MODEL		I <sub>max</sub> (cd)	490.3	S/MH(C0/180)	1.33
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.36
RATED VOLTAGE(V)		TOTAL FLUX(lm)	1557.0	η UP,DN(C0-180)	0.3,45.8
NOMINAL FLUX(lm)	1556.98	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.6,53.3
LAMPS INSIDE	1	η up(%)	0.9	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)		η down(%)	99.1	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### ZONAL FLUX DIAGRAM

#### ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	480.8	477.7	478.1	481.5	485.5	488.3	487.8	484.8	0- 10	46.41	46.41	2.98,2.98
20	460.1	453.9	454.2	461.1	469.3	475.6	474.6	468.3	10- 20	134.4	180.8	11.6,11.6
30	425.5	416.0	416.2	426.8	439.4	449.8	448.3	438.8	20- 30	207.8	388.6	25,25
40	375.4	363.1	363.0	377.2	394.3	409.7	407.9	394.7	30- 40	257.2	645.8	41.5,41.5
50	310.4	294.9	294.7	311.8	332.9	354.1	352.6	335.6	40- 50	274.9	920.7	59.1,59.1
60	231.9	213.0	212.4	231.3	256.5	283.0	282.7	262.4	50- 60	256.1	1177	75.6,75.6
70	145.4	123.0	120.7	140.6	169.6	198.6	198.9	177.0	60- 70	201.4	1378	88.5,88.5
80	63.91	43.52	37.97	55.01	81.51	106.8	107.3	88.79	70- 80	121.5	1500	96.3,96.3
90	5.049	2.957	1.457	5.265	12.45	29.89	27.69	20.44	80- 90	43.31	1543	99.1,99.1
100	0.7243	1.001	0.8236	1.354	0.7102	3.375	1.870	1.910	90-100	5.605	1549	99.5,99.5
110	1.146	1.213	1.205	1.230	1.102	1.031	0.9459	1.034	100-110	1.209	1550	99.5,99.5
120	1.434	1.546	1.495	1.474	1.434	1.305	1.251	1.368	110-120	1.251	1551	99.6,99.6
130	1.720	1.759	1.754	1.732	1.736	1.593	1.541	1.641	120-130	1.396	1552	99.7,99.7
140	1.993	1.987	1.998	1.976	1.963	1.820	1.785	1.869	130-140	1.410	1554	99.8,99.8
150	2.113	2.154	2.196	2.173	2.053	2.063	2.014	2.052	140-150	1.262	1555	99.9,99.9
160	2.219	2.244	2.257	2.249	2.279	2.245	2.243	2.234	150-160	1.003	1556	99.9,99.9
170	2.415	2.396	2.410	2.386	2.430	2.427	2.426	2.401	160-170	0.6568	1557	100,100
180	2.415	2.487	2.425	2.432	2.415	2.442	2.456	2.447	170-180	0.2307	1557	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 783.25 lm

%lum = 50.3%

%lamp = 50.3%

Conical surface Flux(120deg): 1176.8 lm

%lum = 75.6%


%lamp = 75.6%

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### WEC AND CCEC

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz		
Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.327	.186	.059	.319	.182	.058	.305	.175	.056	.293	.169	.054	.281	.163	.052		
2.0	.303	.166	.051	.297	.163	.050	.284	.158	.049	.273	.153	.048	.263	.149	.047		
3.0	.279	.148	.044	.273	.146	.044	.262	.142	.043	.252	.138	.042	.242	.134	.042		
4.0	.256	.133	.039	.251	.131	.039	.241	.128	.038	.232	.125	.038	.224	.122	.037		
5.0	.236	.120	.035	.231	.119	.035	.223	.116	.034	.215	.113	.034	.207	.111	.033		
6.0	.218	.109	.031	.214	.108	.031	.206	.106	.031	.199	.103	.030	.192	.101	.030		
7.0	.202	.100	.028	.199	.099	.028	.192	.097	.028	.185	.095	.028	.179	.093	.027		
8.0	.189	.092	.026	.185	.091	.026	.179	.090	.026	.174	.088	.025	.168	.086	.025		
9.0	.177	.085	.024	.174	.085	.024	.168	.083	.024	.163	.082	.023	.158	.080	.023		
10.0	.166	.080	.022	.163	.079	.022	.158	.077	.022	.153	.076	.022	.149	.075	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.197	.197	.197	.169	.169	.169	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.188	.163	.140	.161	.140	.120	.110	.096	.083	.063	.056	.048	.020	.018	.016	
2.0	.181	.139	.104	.155	.119	.090	.106	.083	.062	.061	.048	.037	.020	.016	.012	
3.0	.173	.121	.080	.148	.105	.069	.102	.073	.049	.059	.042	.029	.019	.014	.009	
4.0	.166	.108	.064	.142	.093	.056	.098	.065	.039	.057	.038	.023	.018	.012	.008	
5.0	.158	.098	.053	.136	.085	.046	.093	.059	.033	.054	.035	.019	.017	.011	.006	
6.0	.151	.090	.046	.130	.078	.040	.089	.054	.028	.052	.032	.017	.017	.010	.006	
7.0	.144	.083	.040	.124	.072	.035	.086	.050	.025	.050	.030	.015	.016	.010	.005	
8.0	.137	.077	.035	.118	.067	.031	.082	.047	.022	.048	.028	.013	.015	.009	.004	
9.0	.131	.072	.032	.113	.062	.028	.078	.044	.020	.046	.026	.012	.015	.009	.004	
10.0	.125	.068	.029	.108	.059	.026	.075	.041	.018	.044	.024	.011	.014	.008	.004	

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz										
Lamp Flux:1556.98x1 lm										
NAME: 02 RGB+CCT 合					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 0.02*1			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	22.0	23.5	22.3	23.8	24.0	21.6	23.2	21.9	23.4	23.6
3H	23.5	25.0	23.8	25.2	25.5	23.0	24.4	23.3	24.6	24.9
4H	24.1	25.5	24.5	25.8	26.0	23.4	24.7	23.7	25.0	25.3
6H	24.6	25.9	24.9	26.2	26.5	23.6	24.9	23.9	25.2	25.5
8H	24.8	26.0	25.1	26.3	26.6	23.6	24.9	24.0	25.2	25.5
12H	24.9	26.1	25.2	26.4	26.7	23.6	24.8	24.0	25.1	25.4
4H 2H	22.5	23.9	22.8	24.1	24.4	22.2	23.6	22.6	23.9	24.1
3H	24.2	25.4	24.5	25.7	26.0	23.7	24.9	24.0	25.2	25.5
4H	24.9	26.0	25.3	26.3	26.7	24.2	25.3	24.6	25.6	26.0
6H	25.5	26.4	25.9	26.8	27.2	24.5	25.5	24.9	25.9	26.2
8H	25.7	26.6	26.1	27.0	27.4	24.6	25.5	25.0	25.9	26.3
12H	25.9	26.7	26.3	27.1	27.5	24.6	25.4	25.0	25.8	26.3
8H 4H	25.1	26.0	25.5	26.3	26.8	24.4	25.3	24.8	25.7	26.1
6H	25.7	26.5	26.2	26.9	27.4	24.8	25.6	25.3	26.0	26.5
8H	26.0	26.7	26.5	27.2	27.6	24.9	25.6	25.4	26.1	26.5
12H	26.3	26.9	26.8	27.3	27.8	25.0	25.6	25.5	26.0	26.5
12H 4H	25.0	25.9	25.5	26.3	26.7	24.4	25.3	24.9	25.7	26.1
6H	25.8	26.4	26.2	26.9	27.3	24.9	25.5	25.3	26.0	26.5
8H	26.1	26.7	26.6	27.1	27.6	25.0	25.6	25.5	26.1	26.5
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.3				

CIE Pub.117, 1557 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.5)  
Area: 0.02 m2

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	43	36	30
0.80	66	54	46	65	53	46	63	52	46	38
1.00	74	63	55	73	62	55	71	63	54	47
1.25	81	70	63	80	70	62	77	68	62	54
1.50	86	76	69	85	75	68	81	73	67	59
2.00	93	84	78	92	83	77	88	81	75	67
2.50	97	89	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	94	89	84	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	103	98	105	101	97	100	97	93	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:



AAI Figure

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### LED Avg.L Report

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	23835
L_0~180 (75) av	22003
L_0~180 (85) av	20849
L_90~270 (65) av	24216
L_90~270 (75) av	22160
L_90~270 (85) av	21523
L_45 (65) av	24186
L_45 (75) av	22231
L_45 (85) av	22161

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.001V I:1.2186A P:29.248W PF:1.0000 Freq:0Hz Lamp Flux:1556.98x1 lm		
NAME: 02 RGB+CCT 合	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	489	489	489	489	489	489	489	489	489	489	489	489	489	489	489	489			
5	486	486	485	485	485	486	487	488	489	490	490	490	490	490	488	488			
10	481	479	478	478	478	480	481	484	485	487	488	489	488	487	485	483			
15	472	470	467	467	468	470	473	476	479	482	484	484	483	481	478	475			
20	460	457	454	453	454	457	461	465	469	473	476	476	475	472	468	464			
25	445	440	437	436	437	441	446	451	456	461	464	465	463	460	455	450			
30	425	420	416	415	416	421	427	433	439	446	450	450	448	444	439	432			
35	402	396	391	390	392	397	404	411	419	426	432	432	430	425	419	411			
40	375	368	363	362	363	369	377	386	394	403	410	411	408	402	395	385			
45	345	337	331	329	331	337	347	356	366	376	384	385	382	376	367	356			
50	310	301	295	293	295	302	312	322	333	345	354	356	353	346	336	323			
55	273	263	256	253	255	263	273	284	296	310	321	323	319	312	301	287			
60	232	221	213	211	212	221	231	243	257	271	283	286	283	274	262	247			
65	189	177	168	165	167	175	187	199	214	229	242	246	242	234	221	205			
70	145	133	123	120	121	129	141	155	170	185	199	202	199	190	177	161			
75	103	91.6	80.3	76.2	75.9	84.6	95.5	110	125	139	152	156	154	144	132	117			
80	63.9	53.1	43.5	38.6	38.0	44.7	55.0	67.2	81.5	94.7	107	110	107	98.7	88.8	76.6			
85	30.2	23.2	16.8	12.9	11.9	16.3	23.0	32.3	42.5	54.9	64.5	66.5	63.2	57.2	50.2	41.7			
90	5.05	5.48	2.96	1.89	1.46	2.86	5.27	9.35	12.5	23.1	29.9	30.7	27.7	24.2	20.4	14.3			
95	0.68	0.88	1.28	1.02	0.73	1.22	2.22	2.81	0.57	7.42	10.3	10.1	8.44	6.91	5.43	3.70			
100	0.72	0.94	1.00	1.06	0.82	1.01	1.35	0.93	0.71	2.71	3.38	3.09	1.87	1.99	1.91	1.14			
105	0.94	1.12	1.03	1.14	0.99	1.13	1.08	1.06	0.92	1.05	1.53	1.26	0.75	1.01	0.96	0.91			
110	1.15	1.32	1.21	1.32	1.21	1.31	1.23	1.26	1.10	0.94	1.03	0.96	0.95	0.99	1.03	0.96			
115	1.27	1.47	1.39	1.49	1.37	1.46	1.31	1.44	1.28	1.09	1.14	0.96	1.10	0.99	1.19	1.18			
120	1.43	1.63	1.55	1.66	1.49	1.60	1.47	1.56	1.43	1.24	1.30	1.17	1.25	1.22	1.37	1.31			
125	1.58	1.77	1.68	1.78	1.69	1.75	1.66	1.73	1.60	1.41	1.46	1.28	1.39	1.30	1.49	1.43			
130	1.72	1.89	1.76	1.90	1.75	1.87	1.73	1.87	1.74	1.51	1.59	1.41	1.54	1.43	1.64	1.59			
135	1.98	2.01	1.99	2.01	2.01	2.01	1.98	1.99	1.86	1.68	1.70	1.55	1.66	1.57	1.76	1.72			
140	1.99	2.09	1.99	2.08	2.00	2.07	1.98	2.05	1.96	1.76	1.82	1.70	1.79	1.72	1.87	1.82			
145	2.01	2.15	2.03	2.14	2.01	2.13	2.01	2.11	2.04	2.00	1.97	1.84	1.92	1.83	1.99	1.98			
150	2.11	2.23	2.15	2.17	2.20	2.26	2.17	2.20	2.05	1.98	2.06	2.01	2.01	2.00	2.05	1.98			
155	2.17	2.29	2.18	2.31	2.20	2.32	2.20	2.29	2.20	2.04	2.15	2.01	2.12	2.00	2.11	2.10			
160	2.22	2.38	2.24	2.40	2.26	2.41	2.25	2.35	2.28	2.16	2.24	2.19	2.24	2.13	2.23	2.19			
165	2.28	2.44	2.31	2.43	2.38	2.44	2.28	2.42	2.35	2.23	2.34	2.20	2.35	2.25	2.31	2.23			
170	2.41	2.42	2.40	2.49	2.41	2.45	2.39	2.46	2.43	2.29	2.43	2.29	2.43	2.27	2.40	2.28			
175	2.42	2.42	2.43	2.49	2.43	2.45	2.42	2.46	2.43	2.39	2.44	2.39	2.46	2.38	2.45	2.40			
180	2.42	2.42	2.49	2.49	2.43	2.45	2.43	2.45	2.42	2.41	2.44	2.43	2.46	2.44	2.45	2.42			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks: