


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 77.83 lm/W			
MODEL		I _{max} (cd)	180.5	S/MH(C0/180)	1.28
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.34
RATED VOLTAGE(V)		TOTAL FLUX(lm)	551.21	η UP,DN(C0-180)	0.3,46.1
NOMINAL FLUX(lm)	551.212	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.5,53.0
LAMPS INSIDE	1	η up(%)	0.9	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)		η down(%)	99.1	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	177.4	175.8	175.3	175.8	177.3	178.7	179.4	178.6	0- 10	17.06	17.06	3.1,3.1
20	169.0	166.1	165.1	166.2	168.9	172.1	173.3	171.9	10- 20	49.12	66.18	12,12
30	155.1	150.9	149.6	151.2	155.3	160.2	162.1	159.8	20- 30	75.15	141.3	25.6,25.6
40	135.9	130.6	129.1	131.1	136.4	143.0	145.7	142.5	30- 40	91.85	233.2	42.3,42.3
50	112.0	105.6	103.8	106.3	113.0	121.1	124.4	120.3	40- 50	96.92	330.1	59.9,59.9
60	83.99	76.67	74.56	77.59	85.52	94.86	98.49	93.62	50- 60	89.29	419.4	76.1,76.1
70	53.66	45.44	42.49	46.62	55.75	65.18	68.59	63.28	60- 70	69.79	489.2	88.7,88.7
80	24.48	17.10	13.28	18.02	26.68	34.50	36.53	32.57	70- 80	42.14	531.3	96.4,96.4
90	2.025	1.767	0.5045	1.343	3.932	9.284	9.104	8.021	80- 90	15.05	546.4	99.1,99.1
100	0.2581	0.4255	0.2885	0.3034	0.2885	0.8033	0.4846	1.014	90-100	1.883	548.2	99.5,99.5
110	0.3189	0.3795	0.3642	0.3485	0.4103	0.3796	0.3644	0.3944	100-110	0.4354	548.7	99.5,99.5
120	0.4555	0.4705	0.4707	0.4551	0.5467	0.5009	0.4859	0.4707	110-120	0.4394	549.1	99.6,99.6
130	0.5313	0.5464	0.5766	0.5613	0.6226	0.6069	0.5618	0.5764	120-130	0.4779	549.6	99.7,99.7
140	0.6679	0.6986	0.6984	0.7281	0.7139	0.6678	0.6529	0.6523	130-140	0.4824	550.1	99.8,99.8
150	0.7592	0.7589	0.7432	0.7433	0.7746	0.7591	0.7440	0.7735	140-150	0.4543	550.5	99.9,99.9
160	0.7592	0.7742	0.7440	0.7585	0.8505	0.8350	0.8351	0.8493	150-160	0.3621	550.9	99.9,99.9
170	0.8046	0.8044	0.8806	0.8040	0.8655	0.8803	0.9110	0.8647	160-170	0.2356	551.1	100,100
180	0.8807	0.8803	0.9262	0.8495	0.8655	0.8803	0.8958	0.8647	170-180	0.0818	551.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 281.79 lm

%lum = 51.1%

%lamp = 51.1%

Conical surface Flux(120deg): 419.39 lm

%lum = 76.1%


%lamp = 76.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JINZHI
 Test Date:2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:9.660m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JINZHI
Test Date: 2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 9.660m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm					
NAME: 02 RGB+CCT 暖白		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.: 0.02*1		Shielding Angle:	

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.01	1.01	1.01	.99
1.0	1.03	.98	.94	1.01	.96	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.76	.87	.81	.75	.84	.78	.73	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.63	.76	.69	.62	.73	.67	.61	.70	.65	.60	.68	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.52	.46	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.45	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.324	.184	.058	.316	.180	.057	.303	.174	.055	.290	.167	.054	.278	.161	.052		
2.0	.301	.165	.051	.294	.162	.050	.282	.157	.049	.271	.152	.048	.260	.147	.046		
3.0	.277	.147	.044	.271	.145	.044	.260	.141	.043	.250	.137	.042	.241	.133	.041		
4.0	.254	.132	.039	.249	.130	.039	.239	.127	.038	.230	.124	.037	.222	.121	.037		
5.0	.234	.119	.035	.230	.118	.034	.221	.115	.034	.213	.112	.033	.206	.110	.033		
6.0	.217	.109	.031	.213	.107	.031	.205	.105	.031	.198	.103	.030	.191	.101	.030		
7.0	.201	.100	.028	.198	.099	.028	.191	.097	.028	.184	.095	.028	.178	.093	.027		
8.0	.188	.092	.026	.185	.091	.026	.178	.089	.025	.173	.087	.025	.167	.086	.025		
9.0	.176	.085	.024	.173	.084	.024	.167	.083	.023	.162	.081	.023	.157	.080	.023		
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.153	.076	.022	.148	.075	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.197	.197	.197	.169	.169	.169	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.188	.163	.140	.161	.140	.121	.110	.096	.083	.063	.056	.048	.020	.018	.016	
2.0	.180	.139	.104	.154	.119	.090	.106	.083	.063	.061	.048	.037	.020	.016	.012	
3.0	.173	.121	.080	.148	.105	.070	.102	.073	.049	.059	.042	.029	.019	.014	.009	
4.0	.165	.108	.064	.142	.093	.056	.097	.065	.039	.056	.038	.023	.018	.012	.008	
5.0	.157	.098	.053	.135	.084	.047	.093	.059	.033	.054	.035	.019	.017	.011	.006	
6.0	.150	.089	.046	.129	.077	.040	.089	.054	.028	.052	.032	.017	.017	.010	.006	
7.0	.143	.082	.040	.123	.071	.035	.085	.050	.025	.049	.030	.015	.016	.010	.005	
8.0	.137	.077	.035	.118	.066	.031	.081	.047	.022	.047	.028	.013	.015	.009	.004	
9.0	.131	.072	.032	.113	.062	.028	.078	.044	.020	.045	.026	.012	.015	.008	.004	
10.0	.125	.067	.029	.108	.059	.026	.075	.041	.018	.044	.024	.011	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz										
Lamp Flux:551.212x1 lm										
NAME: 02 RGB+CCT 暖白					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 0.02*1			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	22.1	23.7	22.4	23.9	24.1	21.7	23.2	22.0	23.4	23.7
3H	23.7	25.1	24.0	25.4	25.6	23.0	24.4	23.3	24.7	24.9
4H	24.3	25.7	24.7	26.0	26.2	23.4	24.8	23.8	25.0	25.3
6H	24.8	26.1	25.2	26.4	26.7	23.6	24.9	24.0	25.2	25.5
8H	25.0	26.3	25.4	26.6	26.9	23.7	24.9	24.0	25.2	25.5
12H	25.2	26.3	25.5	26.7	27.0	23.7	24.9	24.0	25.2	25.5
4H 2H	22.6	24.0	23.0	24.2	24.5	22.3	23.6	22.6	23.9	24.2
3H	24.4	25.6	24.7	25.9	26.2	23.8	24.9	24.1	25.3	25.6
4H	25.1	26.2	25.5	26.6	26.9	24.3	25.4	24.7	25.7	26.1
6H	25.8	26.7	26.2	27.1	27.5	24.6	25.6	25.0	25.9	26.3
8H	26.0	26.9	26.4	27.3	27.7	24.7	25.6	25.1	26.0	26.4
12H	26.2	27.0	26.6	27.4	27.9	24.7	25.5	25.1	25.9	26.3
8H 4H	25.3	26.2	25.7	26.6	27.0	24.5	25.4	25.0	25.8	26.2
6H	26.1	26.8	26.5	27.2	27.7	25.0	25.7	25.4	26.1	26.6
8H	26.4	27.1	26.9	27.5	28.0	25.1	25.8	25.6	26.2	26.7
12H	26.7	27.2	27.2	27.7	28.2	25.2	25.7	25.6	26.2	26.7
12H 4H	25.3	26.1	25.7	26.5	26.9	24.6	25.4	25.0	25.8	26.2
6H	26.1	26.8	26.6	27.2	27.7	25.0	25.7	25.5	26.1	26.6
8H	26.4	27.0	26.9	27.5	28.0	25.2	25.8	25.7	26.2	26.7
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 551.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.1)
Area: 0.02 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	44	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	55	71	64	55	47
1.25	82	71	63	80	70	63	77	69	62	55
1.50	87	76	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	68
2.50	98	90	83	96	88	82	92	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	103	98	105	101	97	101	97	94	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	8261
L_0~180 (75) av	7673
L_0~180 (85) av	7431
L_90~270 (65) av	8439
L_90~270 (75) av	7678
L_90~270 (85) av	7329
L_45 (65) av	8350
L_45 (75) av	7678
L_45 (85) av	7717

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JINZHI
 Test Date:2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:9.660m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JINZHI
Test Date: 2021-07-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 9.660m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.2951A P:7.0824W PF:1.0000 Freq:0Hz Lamp Flux:551.212x1 lm		
NAME: 02 RGB+CCT 暖白	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180	180			
5	179	179	179	178	178	178	179	179	179	180	180	181	180	180	180	180			
10	177	177	176	175	175	175	176	176	177	178	179	180	179	179	179	178			
15	174	173	172	171	171	171	172	173	174	175	176	177	177	177	176	175			
20	169	167	166	165	165	165	166	167	169	171	172	173	173	173	172	171			
25	163	161	159	158	158	158	159	161	163	165	167	168	168	168	167	165			
30	155	153	151	150	150	150	151	153	155	158	160	162	162	162	160	158			
35	146	144	141	140	140	141	142	144	146	149	152	154	155	154	152	149			
40	136	133	131	130	129	130	131	133	136	140	143	145	146	145	143	140			
45	125	121	119	118	117	118	119	122	125	129	133	135	136	135	132	129			
50	112	109	106	104	104	105	106	109	113	117	121	124	124	123	120	116			
55	98.5	94.7	91.6	90.2	89.7	90.8	92.4	95.4	99.6	104	108	111	112	110	107	103			
60	84.0	79.9	76.7	74.9	74.6	75.7	77.6	80.9	85.5	90.1	94.9	97.7	98.5	96.7	93.6	89.0			
65	68.9	64.6	61.1	59.1	58.7	59.9	62.2	65.8	70.7	75.5	80.3	83.3	83.9	82.2	78.7	74.1			
70	53.7	49.4	45.4	43.2	42.5	44.0	46.6	50.7	55.8	60.5	65.2	68.0	68.6	66.8	63.3	58.8			
75	38.6	34.8	30.4	28.0	26.8	28.7	31.5	35.9	40.8	45.3	49.5	52.1	52.7	50.8	47.6	43.5			
80	24.5	20.8	17.1	14.6	13.3	15.1	18.0	22.0	26.7	30.7	34.5	36.3	36.5	34.8	32.6	29.0			
85	11.9	9.60	7.00	5.00	4.09	5.29	7.29	10.3	14.0	17.6	20.6	21.6	21.5	20.2	18.9	16.3			
90	2.03	2.74	1.77	0.91	0.50	0.67	1.34	2.47	3.93	7.08	9.28	9.65	9.10	8.57	8.02	6.18			
95	0.26	0.41	0.78	0.47	0.29	0.30	0.35	0.36	0.24	1.96	2.72	2.94	2.47	2.63	2.59	1.99			
100	0.26	0.33	0.43	0.40	0.29	0.36	0.30	0.36	0.29	0.81	0.80	0.91	0.48	0.93	1.01	0.62			
105	0.27	0.43	0.38	0.41	0.29	0.43	0.30	0.41	0.36	0.50	0.46	0.44	0.29	0.52	0.41	0.35			
110	0.32	0.47	0.38	0.49	0.36	0.47	0.35	0.47	0.41	0.35	0.38	0.35	0.36	0.41	0.39	0.35			
115	0.39	0.53	0.44	0.55	0.46	0.55	0.45	0.55	0.50	0.35	0.41	0.35	0.41	0.40	0.42	0.35			
120	0.46	0.56	0.47	0.59	0.47	0.58	0.46	0.61	0.55	0.43	0.50	0.35	0.49	0.39	0.47	0.42			
125	0.49	0.61	0.50	0.62	0.52	0.62	0.52	0.67	0.58	0.46	0.55	0.46	0.52	0.41	0.53	0.46			
130	0.53	0.67	0.55	0.70	0.58	0.68	0.56	0.68	0.62	0.50	0.61	0.47	0.56	0.49	0.58	0.47			
135	0.58	0.68	0.61	0.73	0.62	0.73	0.68	0.73	0.67	0.55	0.61	0.49	0.61	0.49	0.61	0.50			
140	0.67	0.73	0.70	0.79	0.70	0.77	0.73	0.77	0.71	0.61	0.67	0.55	0.65	0.53	0.65	0.55			
145	0.74	0.79	0.74	0.79	0.73	0.81	0.74	0.79	0.76	0.70	0.73	0.64	0.70	0.56	0.70	0.71			
150	0.76	0.81	0.76	0.82	0.74	0.84	0.74	0.84	0.77	0.73	0.76	0.73	0.74	0.68	0.77	0.74			
155	0.76	0.81	0.76	0.84	0.74	0.87	0.74	0.84	0.82	0.74	0.79	0.74	0.80	0.73	0.79	0.74			
160	0.76	0.81	0.77	0.88	0.74	0.88	0.76	0.88	0.85	0.77	0.83	0.74	0.84	0.74	0.85	0.74			
165	0.79	0.93	0.77	0.91	0.88	0.88	0.79	0.90	0.87	0.77	0.87	0.74	0.88	0.76	0.85	0.77			
170	0.80	0.91	0.80	0.91	0.88	0.88	0.80	0.90	0.87	0.79	0.88	0.79	0.91	0.77	0.86	0.85			
175	0.82	0.90	0.82	0.91	0.88	0.93	0.80	0.90	0.87	0.81	0.88	0.81	0.91	0.82	0.86	0.85			
180	0.88	0.90	0.88	0.91	0.93	0.93	0.85	0.88	0.87	0.85	0.88	0.87	0.90	0.85	0.86	0.88			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-07-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks: