


Skyline™

3060 Rooflight

Yuji Skyline™ lighting system is based on sunlight simulator technology to artificially recreate the visual experience of natural sun light and clear sky. With breakthroughs in mimicking sun light and sky simulation optics, Yuji Skyline™ brings a true blue sky indoor, ensuring a sufficient daily relationship with natural sun light for visual comfort and mood health. They are excellent for scenarios that require natural sunlight experiences, preferably for residential, public, entertainment, retail, office, artistic occasions and etc.



Features



- Natural blue sky visual effect
- Up to CRI 98 light quality
- Full sunlight spectrum
- Circadian cycle adjustable
- Premium thermal management
- Recessed installation
- CCT tunable & Lumen Dimmable
- Smart controlling APP available
- 30,000 hours life time

Specification

Part Number	Power Consumption	CRI	Beam Angle	Color-Temp	Luminous Flux	ON/OFF	Lifetime
Skyline 3060	50W	98	40°	2700K-6500K	2500lm	100,000	30,000hr

Skyline™ 3060 Rooflight

General Information

Cap base:	-	Nominal lifetime:	30,000 h
EU RoHS compliant:	Yes	Switching cycle:	100,000 X
Dimension:	L600×W300×H185 mm L23.6×W11.8×H7.3 inch	Net weight per lamp:	123 oz / 3500 g


Technical data—Photometrical

Color-Temp:	2700K~6500K	Color rendering index:	98
Initial luminous flux:	2500 lm	R9:	90+
Color consistency:	SDCM<6	TM-30-20 Rf:	97
Beam angle:	40°	TM-30-20 Rg:	102


Technical data—Electrical

Power:	50 W	Nominal voltage:	100-240 V
Power factor:	≥ 0.95	Input frequency:	50/60 Hz
Lamp current:	240 mA@230V 460 mA@120V	Starting time:	<0.5 s
Dimmable:	Yes	Warm-up time (60 %):	<0.5 s

Spectral power distribution (2700K)



Color accuracy (2700K)



Circadian cycle setting

