

Installation Instructions for 5" Housing

WARNING: For your safety read and understand instructions completely before starting installation. Before wiring to Power supply, turn off electricity at the fuse or circuit breaker box.

recessed fixtures are designed to meet the latest NEC requirements and are UL listed in full compliance with UL 1571 or 1570. Before attempting installation of any recessed lighting fixture check your local electrical code. This code sets the wiring standards for your locality and should be carefully studied before starting.

Installation in New Construction

Note : if fixture is to be switched from wall switch, make sure that black power supply wire is connected to the switch. DO NOT connect the white supply wire to the switch

- Make certain no bare wires are exposed outside the wire nut connectors.
- Fixture is designed for installation where it may come in contact with insulation (Fig. 1)
- Bar Hangers for this fixture are of interlocking design to allow positioning of housing along entire length of bars. Position bar hangers so nail-in tabs point away from housing (fig.2)
- Bar hangers may be shortened to fit 12" framing by breaking at score lines

- Step 1** Extend bar hangers to fit between joists. Position fixture by hammering nail-in tabs into joists. Hangers should be level with bottom of joists (figure 2)
- Step 2** Follow steps 1 through 4 under Electrical Connection.
- Step 3** Position fixture on hanger bars, To secure fixture position in ceiling, tighten screw and/or squeeze tabs into hanger.

