

17004

6" Non-IC Shallow Housing

Product Description

Suitable for new construction in residential and commercial applications.
NON-IC. Insulation must be kept a minimum of 3" from housing.

Housing

Integral thermal protector guards against improper lamping and misuse of insulation materials.
Adjustable socket bracket assures proper and consistent lamp positioning.
5 3/4" height allows use in 2" x 6" joist construction.

Plaster Frame

Housing is secured to plaster frame with screws and can be removed for access to junction box.
Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness.

Junction Box

Listed for through branch circuit wiring and includes several 3/4" knockouts.
Four pryouts with integral strain relief simplify Romex installation.
Supplied with three push-in wire connectors.

Hanger Bars

Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws.
Unique hanger bar lip design helps align can to joist.
Four double-headed captive nails provide for ease of installation.
Bars can be repositioned 90° on plaster frame without tools.
Bars fit onto T-bar spine for quick alignment and can be permanently secured.
Score lines allow bars to be shortened without tools to accommodate a 12" joist span.

Ordering Information

Catalog Number	Description
17004	6" Non-IC Shallow Housing

Project

Catalog

Type

