



MSD Gold™ MiniFastFit

MSD Gold™ 300/2 MiniFastFit 1CT/16

The specially designed lamp base of the MSD Gold™ MiniFastFit means that this lamp can be replaced in just seconds, helping to ensure non-stop entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. The lamp's compact size allows for easy handling and compact fixture designs, while the very short arc provides a high perceived brightness and high beam intensity. What's more, the MSD Gold™ MiniFastFit has an extended lifetime, which further reduces lamp replacement costs.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information		Correlated Color Temperature (Nom)		8600 K
Cap-Base	PGJX28 [PGJX28]	Luminous Efficacy (rated) (Nom)	70 lm/W	
Operating Position	UNIVERSAL [Any or Universal (U)]	Color Rendering Index (Nom)	73	
Main Application	Entertainment	Operating and electrical		
Life to 50% Failures (Nom)	2000 h	Power (Nom)	300 W	
System Description	MiniFastFit	Lamp Current (Nom)	3.8 A	
Light technical		Ignition Supply Voltage (Min)	207 V	
Color Code	2	Controls and dimming		
Luminous Flux (Nom)	21000 lm	Dimmable	No	
Chromaticity Coordinate X (Nom)	292			
Chromaticity Coordinate Y (Nom)	310			

MSD Gold™ MiniFastFit

Mechanical and housing

Cap-Base Information PGJX28

Luminaire design requirements

Bulb Temperature (Max) 600 °C

Pinch Temperature (Max) 350 °C

Pinch Temperature (Max)-DUP(do not use) 350 °C

Product data

Full product code 872790091257900

Order product name MSD Gold™ 300/2 MiniFastFit 1CT/16

EAN/UPC - Product 8727900912579

Order code 928199805114


Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 16

Material Nr. (12NC) 928199805114

Net Weight (Piece) 0.062 kg

Dimensional drawing



MSD Gold™ 300/2 MiniFastFit 1CT/16

Product	D (max)	O	L (min)	L (max)	L	C (max)
MSD Gold™ 300/2	23 mm	5.0 mm	65.8 mm	67.8 mm	66.8 mm	126 mm
MiniFastFit 1CT/16						

Photometric data

