



28706 - GE T1 - Low Voltage

685 5

GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Base Description	Sub-Midget Flanged
Filament	C-2R
Rated Life Hours-nominal	40000 h
Atmosphere	Vacuum
Primary Application	Low Voltage
Bulb Shape	T1

PHOTOMETRIC CHARACTERISTICS

Mean Spherical Candlepower	0.050 cd
----------------------------	----------

PRODUCT INFORMATION

Product Code	28706
Description	685 5
Alternative Unit Of Measure	PACK
Standard Package Quantity	
Ean UPC	043168287067
Standard Package GTIN	10043168287064
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168287067
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168287067
Standard Package GTIN	00043168287067
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	1000
Ean UPC	043168287067
Standard Package GTIN	30043168287068
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1000
Sales Unit	Case
UCC	

DIMENSIONS

Diameter	0.12 in
Light Center Length (LCL)	0.19 in
Bulb Max Overall Length-MOL	0.38 in

ELECTRICAL CHARACTERISTICS

Input Voltage [nom]	5 V
Rated power (Watts)	0 W

