

## Par Series

### Sunlite 40980 LED Par30 Short Neck Light Bulb, Dimmable, 30K Warm White 6 Pack

High Efficiency

#### **DESCRIPTION:**

*Produces a beautiful dimmable glow from the moment you switch it on: Energy efficient & low maintenance: Warranty:*

#### **FEATURES:**

- **EMITS A SOFT GLOW:** With a color temperature of 3000K the par 30 bulb emits a warm white glow, generating a comfortable atmosphere in every room of your home
- **INSTANT LIGHTING:** This LED PAR30 provides a CRI of 81 and 750 lumens of targeted light which reaches full brightness immediately when powered on
- **LOW ENERGY & COST EFFECIVE:** The bulb uses only 10 watts of energy (75 Watt Equivalent), saving a significant amount on your energy bill. The LED bulb costs only 1.20 per year to operate (based on a 3-hour day)
- **LONG LIFETIME:** The LED bulb has an operational lifetime expectation of up to 25,000 hours before needing to be replaced. That's 22.8 years of use! (based on a 3-hour day)
- **MEETS HIGHEST SAFETY STANDARDS:** Energy-star and UL listed for damp locations. Dimmable to create different atmospheres as needed



**SPECIFICATIONS:**
**General Characteristics**

|                                |                    |
|--------------------------------|--------------------|
| <b>Bulb Shape</b>              | PAR30S             |
| <b>Average Rated Hours</b>     | 25000              |
| <b>Finish</b>                  | White              |
| <b>Base</b>                    | Medium Screw (E26) |
| <b>Average Life Span Years</b> | 23                 |
| <b>Dimmable</b>                | Yes                |
| <b>Dimming Type</b>            | 10-100%            |
| <b>Material</b>                | PC & Aluminum      |

**Electrical Characteristics**

|                              |              |
|------------------------------|--------------|
| <b>Watts</b>                 | 9            |
| <b>Volts</b>                 | 120          |
| <b>Equivalent Wattage</b>    | 75           |
| <b>LED Chip Manufacturer</b> | SMD2835      |
| <b>Power Factor</b>          | 0.7          |
| <b>Temperature</b>           | -4°F - 113°F |

**Light Characteristics**

|                                  |            |
|----------------------------------|------------|
| <b>Lumens Brightness</b>         | 850        |
| <b>Color Rendering Index CRI</b> | 80         |
| <b>CBCP</b>                      | 1640       |
| <b>Emitted Color</b>             | Warm White |
| <b>Color Temperature Kelvin</b>  | 3000K      |
| <b>Beam Angle</b>                | 35°        |
| <b>Beam Angle Description</b>    | Flood      |

**Additional Features**

|                             |                     |
|-----------------------------|---------------------|
| <b>Safety Rating Mark</b>   | ETL - Damp Location |
| <b>Safety Rated For USA</b> | Yes                 |
| <b>Energy Star</b>          | Yes                 |
| <b>Energy Star Number</b>   | 2383804             |

**Product Dimensions**

|                               |                           |
|-------------------------------|---------------------------|
| <b>MOL (in)</b>               | 3.44                      |
| <b>Diameter (in)</b>          | 3.74                      |
| <b>Item Weight (lb)</b>       | 0.340                     |
| <b>Package Dimension (in)</b> | (W) 4.5 (H) 8.2 (D) 12.15 |
| <b>Package Weight (lb)</b>    | 2.380                     |

**Product Data**

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 6            |
| <b>Pack Size</b>      | 6            |
| <b>Item UPC</b>       | 653703409801 |
| <b>Warranty Years</b> | 3            |
| <b>Package Type</b>   | Box          |