

**MR Series** 

**High Efficiency** 

## **DESCRIPTION:**

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

## FEATURES:

- -
- -
- -
- •
- .



# sunlite

## **SPECIFICATIONS:**

### **General Characteristics**

| Ρ | ro | dι | ict | D | im | e | ns | io    | ns |
|---|----|----|-----|---|----|---|----|-------|----|
|   |    |    |     | _ |    |   |    | · · · |    |

Warranty Years Package Type

| Bulb Shape              | MR16                    | MOL (in)            | 2.17                       |
|-------------------------|-------------------------|---------------------|----------------------------|
| Average Rated Hours     | 25000                   | Diameter (in)       | 1.97                       |
| Finish                  | White                   | Item Dimension (in) | (W) 1.97 (H) 2.17 (D) 1.97 |
| Base                    | Medium Screw (E26)      |                     |                            |
| Average Life Span Years | 23                      | Product Data        |                            |
| Dimmable                | Yes                     | Case Unit Rate      | 12                         |
| Dimming Type            | Forward Phase (Triac or | Pack Size           | 6                          |
|                         | Incandescent)           | Item UPC            | 653703451640               |
| Material                | Plastic & Aluminum      | Warranty Years      | .3                         |

SALE on SUNLITE @ www.BulbAmerica.com

take additional 5% Off with coupon code 5PDF

## Material

## **Electrical Characteristics**

| Amps                  | 0.095        |
|-----------------------|--------------|
| Watts                 | 7            |
| Volts                 | 120          |
| Equivalent Wattage    | 50           |
| LED Chip Manufacturer | SMD2835      |
| Power Factor          | 0.7          |
| Temperature           | -4°F - 113°F |

### **Light Characteristics**

| Lumens Brightness         | 550        |
|---------------------------|------------|
| Color Rendering Index CRI | 80         |
| CBCP                      | 595        |
| Emitted Color             | Cool White |
| Color Temperature Kelvin  | 4000K      |
| Beam Angle                | 35°        |
| Beam Angle Description    | Flood      |
| Flicker                   | no         |

## Additional Features

| Safety Rating Mark |  |
|--------------------|--|
| Mercury Free       |  |

ETL - Damp Location Yes

## Catalog # 45164-SU MR16/LED/7W/MED/40K/6PK\*

3

Box

Sunlite.com