



TrueForce High Lumen PAR

25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB

Philips LED TrueForce PAR high lumen lamps are the perfect transition from CDM lamps to LED.

Product data


General Information		Power Consumption	
Cap-Base	E26 [Single Contact Medium Screw]	Power Consumption	25.5 W
Nominal lifetime	25,000 hour(s)	Wattage Equivalent	75 W
Switching Cycle	50,000	Starting Time (Nom)	0.5 s
Lighting Technology	LED	Warm-up time to 60% light	0.5 s
EU RoHS compliant	Yes	Power Factor (Fraction)	0.8
		Voltage (Nom)	120-277 V
Light Technical		Temperature	
Color Code	830 [CCT of 3000K]	T-Case Maximum (Nom)	95 °C
Beam Angle (Nom)	25 degree(s)		
Luminous Flux	2,500 lumen	Controls and Dimming	
Luminous Intensity (Nom)	11,500 cd	Dimmable	No
Color Designation	White (WH)		
Correlated Color Temperature (Nom)	3000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	98.00 lm/W	Bulb Finish	Clear
Color Consistency	<4	Bulb Material	Aluminum
Color rendering index (CRI)	80	Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Operating and Electrical		Approval and Application	
Line Frequency	50 to 60 Hz	Suitable For Accent Lighting	Yes
Input Frequency	50 to 60 Hz	Energy Consumption kWh/1000 h	- kWh

TrueForce High Lumen PAR

Energy Certifications	Energy Star
Product Data	
Order product name	25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB
Order code	534651
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6



Material Nr. (12NC)	929001917104
Full product name	25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB
EAN/UPC - Case	50046677534658
EAN/UPC - Product/Case	046677534653

Dimensional drawing




Product	D	C
25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB	96 mm	119 mm

Photometric data



Spectral Power Distribution Colour - 25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB



Accent Lighting Spots - 25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB



Light Distribution Diagram - 25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB

TrueForce High Lumen PAR

Lifetime



Life Expectancy Diagram - 25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB

Lumen Maintenance Diagram - 25.5PAR30L/PER/830/F25/ND/120-277V 6/1FB

