



Product Number: 64966

Order Abbreviation: MC150T7.5/U/G12/940

General Description: METALARC POWERBALL 150W ceramic metal halide tubular T7.5, clear, universal operation, G12 base, 4200K CCT, 95 CRI, pulse start, enclosed rated, 15,000 hour rated life

Product Information	
Abbrev. With Packaging Info.	MC150T7.5UG12940 12/CS 1/SKU
ANSI Code	C142/E
ANSI Code 2	C142/E
Approx. Lumens (initial - horizontal)	14700
Approx. Lumens (initial - vertical)	14500
Approx. Lumens (mean - horizontal)	11600
Approx. Lumens (mean - vertical)	11600
Base	G12
Bulb	T7.5
Color Rendering Index (CRI)	95
Color Temperature/CCT (K)	3950
Diameter (in)	0.945
Diameter (mm)	24.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	1112
Maximum Overall Length - MOL (in)	4.125
Maximum Overall Length - MOL (mm)	105
Nominal Voltage (V)	92.00
Nominal Wattage (W)	150.00
Operating Position	Universal



Footnotes

- Consult your LEDVANCE Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- UV-Stop quartz
- Lamps may be operated on a M142 Compliant ballast.
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.