SATCO NUVO

Project Name

ocation.

Prepared By



NUVO 65-686

60W LED AREA LIGHT W/PHOTOCELL

Notes

| General | |
|---------------------------|--------------------|
| Status | Active |
| Finish | Bronze |
| Wattage | 60W |
| Lumen Output | 8400L-9600L |
| CCT (Kelvin) | 3000K/4000K/5000K |
| Temperature | Warm to Cool White |
| IP Rating | IP65 |
| Indoor or Outdoor Fixture | Outdoor |

| Specifications | |
|-----------------------|--|
| Technology | LED |
| CRI | 70 |
| Voltage | 120V-277V |
| Beam Angle | 150x150 |
| Rated Hours | 50000 |
| Operating Temperature | -40C (-40F) to a maximum of +50C (+122F) |
| Dimmable | Yes-Dimmable |
| Photocell | Yes |
| Lens Material | Polycarbonate (PC) |
| Surge Protection | Built-in surge protection - 4KV |
| Weight (lb.) | 5.07 |
| Material | Aluminum |

| Dimensions | |
|-----------------|-------|
| Height (in.) | 7.36 |
| Width (in.) | 9.13 |
| Extension (in.) | 13.62 |

| Compliance | |
|--------------------|--------------------------|
| Safety Listing | cULus |
| Location Rating | Wet |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | PLRIM7S8AL2J |
| California Status | California T24 Compliant |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |

| Additional Information | |
|------------------------|---|
| Additional Information | Type V Lighting Distribution; Dusk to Dawn Lamp |
| Installation Notes | Suitable for 42-60mm pipe installation |
| Warranty | 5 Year Limited - Fixtures |





