

Catalog # 80777-SU CTC/LED/4.5W/50K

B Series

Sunlite 80777 LED B11 Clear Torpedo Tip Chandelier Light Bulb, 4.5 Watts (40W Equivalent) 300 Lumens, Candelabra E12 Base, Dimmable Energy Star and ETL Certified, 5000K Daylight, 1 Count

Chandelier

DESCRIPTION:

Sunlite LED torpedo tip B11 bulbs are designed to give you up to 15,000 hours of reliable service. That means fewer replacements for difficult to reach bulbs. These dimmable and energy efficient lamps provide the same output as a 40 watt bulb while only using 4.5 watts of energy. With 3 hours of daily use the annual operating cost is only \$0.54 per bulb. (Based on \$0. 11/kWh) Installing these Energy Star Certified bulbs may qualify you for state and local rebates. The candelabra base (E12) and classic shape make them perfect for chandeliers, wall sconces, decorative lamps, and even enclosed fixtures. ETL Listed. Ideal for both residential and commercial use.

FEATURES:

- UPGRADE TO LED Easily upgrade your old incandescent bulbs with energy efficient LED technology. These dimmable, bullet bulbs use only 4.5 watts of electricity but are equal to a 40 watt incandescent bulb. LED bulbs are cooler to the touch than traditional incandescent and halogen bulbs when lit
- CLASSIC SHAPE These clear, blunt tip B11 bulbs with a candelabra base (E12) have a classic shape. Perfect for chandeliers, wall sconces, decorative lamps, and many other fixtures. Save energy without sacrificing design
- DIMMABLE Emits a dimmable and bright super white light at 5000K. Soft 300 lumen output. Color Rendering Index (CRI) rating of 80
- LONG LIFE BULBS Long life LED technology saves energy and the hassle of replacing hard to reach bulbs. With an average life of 15,000 hours these bulbs will last up to 13.7 years. The annual energy cost is a low \$0.54 per bulb (Based on 3 hours/day at \$0. 11 per/kWh)
- ENERGY STAR CERTIFIED AND ETL LISTED Installing these Energy Star Certified bulbs may qualify you for state and local rebates. They are also ETL Listed. Ideal for residential and commercial applications. Tested Compatible Dimmer LEVITON 6681 6674 6633P IPL06 IPI06 VPM10 RTD01-10Z IPE04 6161 RPI06-1 1B3211 1C1311 LUTRON S-600P LGCL-153P LGCL-153PL LGCL-153PLH MACL-153M MAELV-600 DVELV-300P DVCL-153P CTCL-153P VTELV-600M CTELV-303P DVELV-303P RRD-6NA DVCL-153P NTLV-600 S-603P DV-600P DV-603P V47-C06579 SLV-600P IPX10-1 SELV-300P MRF2-3LDH DVWCL-153PH SCL-153P



sunlite

SPECIFICATIONS:

General Characteristics

Prod	uct	Dim	ensi	ions
1100	uci		CIIS	0113

Bulb Shape	B11	MOL (in)	3.86
Average Rated Hours	15000	Diameter (in)	1.42
Finish	Clear	Item Dimension (in)	(W) 1.38 (H) 3.78 (D) 1.38
Base	Candelabra Screw (E12)	Package Dimension (in)	(W) 1.5 (H) 4.25 (D) 1.5
Average Life Span Years	14	Package Weight (lb)	0.11
Dimmable	Yes		
Material	Aluminum & Plastic	Product Data	
		Case Unit Rate	6
Electrical Characteristics		Pack Size	1

Item UPC

Warranty Years Package Type

Electrical Characteristics

Watts	4.5
Volts	120
Equivalent Wattage	40
LED Chip Manufacturer	SMD2835
Power Factor	0.7
Temperature	20~45

Light Characteristics

Lumens Brightness	300
Color Rendering Index CRI	84
R9 Rating	12
CBCP	260°
Emitted Color	Daylight
Color Temperature Kelvin	5000K
Beam Angle	270°
Flicker	<30%

Additional Features

Safety Rating Mark	ETL - Damp Location
Safety Rated For USA	Yes
Energy Star	Yes
Energy Star Number	2399394

6
1
653703807775
3
Box

Catalog # 80777-SU CTC/LED/4.5W/50K