

## AR Series

### Sunlite 49149 LED Roadway Security Light with Photo Control Fixture, Wall/Pole Mount, Power Tunable 72W/96W/120W, 15000 Lumens, Color Tunable 30K/40K/50K, UL Listed, Dimmable, For Parks and Roadway AR111 Aluminum Reflector



#### DESCRIPTION:

Sunlite's LED Roadway Security Light with Photo Control Fixture gives the security light you need whenever you need it. These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located within the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 72 watts, 96 watts, or 120 watts. With its bright LEDs and high lumen output from 8640 - 15000, our lights are great for entrance, barns, industrial, security, and many more! Made to last thanks to its aluminum material with a dark brown finish. Designed for pole mounting. The lighting output can be changed when connected to an LED-compatible dimmer switch (0-10v), allowing it to adjust the brightness to suit your need. UL Listed for safety and quality. IP65 rated. Great for commercial applications on 120-277-volt service. Dimensions: 4.16" H x 7.01" W x 10.37" D.

#### FEATURES:

- **DUSK TO DAWN SENSOR** - These roadway light's dusk-to-dawn photocell sensors provide security that, no matter the weather, you will always have light where and when you need it.
  - **TUNABLE COLOR & POWER** - These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located within the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 72 watts, 96 watts, or 120 watts.
  - **MULTIPLE OUTDOOR USE** - With its bright LEDs and high lumen output from 8640 - 15000, our lights are great for entrance, barns, industrial, security, and many more! Made to last thanks to its aluminum material with a dark brown finish. Designed for wall or pole mounting.
  - **DIMMABLE** - The lighting output can be changed when connected to an LED-compatible dimmer switch (0-10v), allowing it to adjust the brightness to suit your need.
- UL Listed for safety and quality. IP65 rated.  
Great for commercial applications on 120-277-volt service.  
Dimensions: 4.16" H x 7.01" W x 10.37" D.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	AR111
<b>Average Rated Hours</b>	15000
<b>Base</b>	Screw Terminal (G53)
<b>Average Life Span Years</b>	14
<b>Dimmable</b>	No

### Electrical Characteristics

<b>Watts</b>	10
<b>Volts</b>	12
<b>Equivalent Wattage</b>	50
<b>Power Factor</b>	0.9

### Light Characteristics

<b>Lumens Brightness</b>	750
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	3000K
<b>Beam Angle</b>	12°
<b>Beam Angle Description</b>	Spot

### Product Dimensions

<b>Package Dimension (in)</b>	(W) 4.4 (H) 3 (D) 4.4
<b>Package Weight (lb)</b>	0.3

### Product Data

<b>Case Unit Rate</b>	6
<b>Pack Size</b>	1
<b>Item UPC</b>	653703810089
<b>Warranty Years</b>	3
<b>Package Type</b>	Box